

X3

Hoogwaardige lange nylonplug

Met de lange nylonplug X3 kunnen dunne of dikke elementen, met 3 mogelijke verankeringsdieptes per lengte, op elk type volle of holle ondergrond worden bevestigd. De plug heeft een gelijkmatige uitzetting in alle richtingen en levert daarom uitstekende prestaties. De plug wordt geleverd met een schroef met zeskantkop of verzonken kop.

Kenmerken

Materiaal

- Plug : nylon,
- Schroeven : elektrolytisch verzinkt staal.

Voordelen

- Hoge sterkte op alle soorten ondergrondmateriaal,
- 3 mogelijke verankeringsdieptes per pluglengte,
- Hoge flexibiliteit, korte installatietijd: de plug kan door het te bevestigen element heen worden geïnstalleerd. Bij installatie met een gereduceerde verankeringsdiepte wordt ook de boortijd verkort,
- Verhoogde uitzetting,
- Ontworpen voor het bevestigen van kapconstructie- en gevelelementen.

Toepassingen

Toepassingsgebieden

- Houten of metalen kapconstructie
- Gevel, buitenisolatie:
- Keper op muur
- Hoekijzer voor gevelbekleding op de muur

Ondergrond

- Ongescheurd beton,
- Hol en vol metselwerk.



Hoogwaardige lange nylonplug

Referentie	Product Reference	Plug [ØxL] [mm]	Screw [ØxL] [mm]	Reduced fixture thickness [t _{fix}] [mm]	Standard fixture thickness [t _{fix}] [mm]	Increased ⁽¹⁾ fixture thickness [t _{fix}] [mm]	Ø drilling fixture [df] [mm]	Bit	Qty per box	Qty per outer box
64602B0808000	X3	8x80	6x88	40	30	-	8.5	T30	50	500
64602B0810000		8x100	6x108	60	50	-	8.5	T30	50	500
64602B0812000		8x120	6x128	80	70	-	8.5	T30	50	500
64602B1008000		10x80	7x88	30	10	-	10.5	T40	50	500
64602B1010000		10x100	7x108	50	30	10	10.5	T40	50	500
64602B1012000		10x120	7x128	70	50	30	10.5	T40	50	500
64602B1014000		10x140	7x148	90	70	50	10.5	T40	50	300
64602B1016000		10x160	7x168	110	90	70	10.5	T40	50	250

NOTE: The thickness of the plaster must be included in the fixing thickness t_{fix}





Table "Afmetingen" cannot be displayed : no references available.



Referentie	Product Reference	Plug [ØxL] [mm]	Screw [ØxL] [mm]	Reduced fixture thickness [t _{fix}] [mm]	Standard fixture thickness [t _{fix}] [mm]	Increased ⁽¹⁾ fixture thickness [t _{fix}] [mm]	Bit	Wrench	Built-in washer [Ø]	Qty per box	Qty per outer box
64703B1006000	X3	10x60	7x68	10	-	-	T40	13	19	50	500
64703B1008000		10x80	7x88	30	10	-	T40	13	19	50	500
64703B1010000		10x100	7x108	50	30	10	T40	13	19	50	500
64703B1012000		10x120	7x128	70	50	30	T40	13	19	50	300
64703B1014000		10x140	7x148	90	70	50	T40	13	19	50	300
64703B1016000		10x160	7x168	110	90	70	T40	13	19	50	250

NOTE: The thickness of the plaster must be included in the fixing thickness t_{fix}

X3 Hoogwaardige lange nylonplug

Design capacities - single anchor - no edge distances





Referentie	Design capacities - single anchor - no edge distances								
	Design capacity								
	Tension - NRd				Shear - VRd				Bending moment - MRd [Nm]
	Non-cracked concrete C12/25 [kN]	Non-cracked concrete C16/20 [kN]	Autoclaved aerated concrete AAC 2 [kN]	Solid brick (BP400) [kN]	Non-cracked concrete C12/15 [kN]	Non-cracked concrete C16/20 [kN]	Autoclaved aerated concrete AAC 2 [kN]	Solid brick (BP400) [kN]	
64602B0808000	0.65	0.83	-	1.4	-	-	-	-	11.3
64602B0810000	0.65	0.83	-	1.4	-	-	-	-	11.3
64602B0812000	0.65	0.83	-	1.4	-	-	-	-	11.3
64602B1008000	1.8	2.5	0.25	1.6	-	-	-	-	18.2
64602B1010000	1.8	2.5	0.25	1.6	-	-	-	-	18.2
64602B1012000	1.8	2.5	0.25	1.6	-	-	-	-	18.2
64602B1014000	1.8	2.5	0.25	1.6	-	-	-	-	18.2
64602B1016000	1.8	2.5	0.25	1.6	-	-	-	-	18.2
64703B1006000	1.8	2.5	0.25	1.6	-	-	-	-	18.2
64703B1008000	1.8	2.5	0.25	1.6	-	-	-	-	18.2
64703B1010000	1.8	2.5	0.25	1.6	-	-	-	-	18.2
64703B1012000	1.8	2.5	0.25	1.6	-	-	-	-	18.2
64703B1014000	1.8	2.5	0.25	1.6	-	-	-	-	18.2
64703B1016000	1.8	2.5	0.25	1.6	-	-	-	-	18.2

1. The design loads have been calculated using the partial safety factors for resistances stated in ETA-approval(s). The loading figures are valid for unreinforced concrete and reinforced concrete with a rebar spacing $s \geq 15$ cm (any diameter) or with a rebar spacing $s \geq 10$ cm, if the rebar diameter is 10mm or smaller.
2. The figures for shear are based on a single anchor without influence of concrete edges. For anchorages close to edges ($c \leq \max [10 \text{ hef}; 60d]$) the concrete edge failure shall be checked per ETAG 001, Annex C, design method A.
3. Concrete is considered non-cracked when the tensile stress within the concrete is $\sigma_L + \sigma_R \leq 0$. In the absence of detailed verification $\sigma_R = 3 \text{ N/mm}^2$ can be assumed (σ_L equals the tensile stress within the concrete induced by external loads, anchors loads included).

*Not covered by ETA-11/0080

X3 Hoogwaardige lange nylonplug

Plaatsing



Spacings and edge distances

Referentie	Product Reference	Plug [ØxL] [mm]	Spacings and edge distances									
			Non-cracked concrete C12/15				Non-cracked concrete C16/20				Autoclaved aerated concrete	
			Min. edge distance [cmin] [mm]	Min. spacing [smin] [mm]	Characteristic edge distance [ccr,N] [mm]	Minimum thickness of support [mm]	Min. edge distance [mm]	Min. spacing [mm]	Characteristic edge distance [mm]	Minimum thickness of support [mm]	Min. edge distance [cmin] [mm]	Min. spacing [smin] [mm]
64602B0808000	X3	8x80	70	85	85	100	50	60	60	100	100	250
64602B0810000	X3	8x100	70	85	85	100	50	60	60	100	100	250
64602B0812000	X3	8x120	70	85	85	100	50	60	60	100	100	250
64602B1008000	X3	10x80	70	70	140	100	50	50	100	100	100	250
64602B1010000	X3	10x100	70	70	140	100	50	50	100	100	100	250
64602B1012000	X3	10x120	70	70	140	100	50	50	100	100	100	250
64602B1014000	X3	10x140	70	70	140	100	50	50	100	100	100	250
64602B1016000	X3	10x160	70	70	140	100	50	50	100	100	100	250
64703B1006000	X3	10x60	70	70	140	100	50	50	100	100	100	250
64703B1008000	X3	10x80	70	70	140	100	50	50	100	100	100	250
64703B1010000	X3	10x100	70	70	140	100	50	50	100	100	100	250
64703B1012000	X3	10x120	70	70	140	100	50	50	100	100	100	250
64703B1014000	X3	10x140	70	70	140	100	50	50	100	100	100	250
64703B1016000	X3	10x160	70	70	140	100	50	50	100	100	100	250

* Not included in the approval

X3 Hoogwaardige lange nylonplug

Installation data

Referentie	Installation data		
	Ø drilling hole [d0] [mm]	Min. drill depth [h1] [mm]	Ø drilling fixture [df] [mm]
64602B0808000	8	55	8.5
64602B0810000	8	55	8.5
64602B0812000	8	55	8.5
64602B1008000	10	65	10.5
64602B1010000	10	65	10.5
64602B1012000	10	65	10.5
64602B1014000	10	65	10.5
64602B1016000	10	65	10.5
64703B1006000	10	65	10.5
64703B1008000	10	65	10.5
64703B1010000	10	65	10.5
64703B1012000	10	65	10.5
64703B1014000	10	65	10.5
64703B1016000	10	65	10.5

