

KIT FIX PPJNCPB Postbase for wind screen

Black square "ready-to-fix" postbases for windscreens PPJNCPB are recommended in the realization of small works such as fences and light garden structures. Very easy to install, they can be bolted on concrete support or screwed on wood.

Features

Matière

- Steel DD11 according to NF EN 10111,
- Black cataphoresis coating,
- Thickness: 2,5 mm (flanges and plate).

Avantages

- 2,5 mm thick reinforced plate, ensuring greater resistance to deformation,
- Plate angles cut out for more security,
- Fully open postbases to the side to install the first fence blade closest to the ground.



Applications

Support

- **Porteur:** béton, acier, bois massif.

Domaines d'utilisation


- Garden fences, panels, windscreens,
- Garden sheds, garden bonfires,
- Light structures and temporary garden structures.



KIT FIX PPJNCPB
Postbase for wind screen

Technical Data

Rozměry a typické hodnoty



| Art. nr. | Rozměry [mm] | | | | | | | | Otvory | |
|------------------|--------------|-------|----|-----|-----|----|----------------|----------------|----------|--------------|
| | A | B | C | D | E | F | t ₁ | t ₂ | Top part | Bottom plate |
| | | | | | | | | | Ø8 | Ø12 |
| KITFIX PPJNC70PB | 71 | 152.5 | 71 | 150 | 150 | 41 | 2.5 | 2.5 | 4 | 4 |
| KITFIX PPJNC90PB | 91 | 152.5 | 91 | 150 | 150 | 49 | 2.5 | 2.5 | 4 | 4 |

KIT FIX PPJNCPB
Postbase for wind screen

Installation

Befestigung

Postbase :

- Black screws Ø6 x 40mm

Plate :

- *Mechanical anchor* : WA M10-78/5
- *Chemical anchor* : resin AT-HP + threaded rod LMAS M10-120/25
- *Installation to timber* : wood screw LAG 10080

KIT FIX PPJNCPB
Postbase for wind screen

