

Technický list

EA444/2PB

Black painted light reinforced angle bracket

SIMPSON

Strong-Tie

Light reinforced black angle brackets are used to assemble small structural joinery for internal and external applications.

Features

Material

- Pre-galvanised mild steel,
- Painted black RAL9005,
- 2 mm thickness

Benefits

- Black colour to be discreet,
- Multiple applications...


Applications

Header member

- **Supporting member:** solid wood, composite lumber, glued-laminated wood, triangular trusses, profiles, etc.
- **Supported member:** wood, concrete, steel, etc.

For Use With

- Interior fittings.
- Furniture.
- Small frames, etc.



Technický list

EA444/2PB


Black painted light reinforced angle bracket

SIMPSON

Strong-Tie®

Technical Data

Product dimensions



Art. nr.	Rozměry [mm]				Otvory	
	A	B	C	Thick.	Hlava	Flange C
					Ø5	Ø5
EA444/2PB-R	40	40	40	2	3	3

EA444/2PB

Black painted light reinforced angle bracket

Installation

Fixing

On wood:


- 3.75 x 30mm square twist nail.
- CNA annular ring-shank nails 4.0 mm.
- CSA screw 5.0 mm.

On concrete:

- HIPC 6-40/10 drive anchors or HIPC 8-60/20.

On metal:

- Bolts.
- HR bolts.
- Rivets, etc.



EA444/2PB

Black painted light reinforced angle bracket