

Technický list

SIMPSON

Strong-Tie

DSPROA4

Hardwood Decking Screw - Stainless Steel A4

Made for hardwood decking such as Cumaro, Bankirai and others. Can be used in Marine environments. Needs pre-drilling with 4 mm drill and pre-countersinking close to the edge.

Features

Material

- Stainless Steel A4

Features:

- 6 lobe drive
- Double threaded
- Chisel point


Applications

Applications:

- Hardwood decking boards to wood

Suitable for:

- Outdoor decking applications



DSPROA4
Hardwood Decking Screw - Stainless Steel A4

Technical Data

Rozměry



Art. nr.	Article number	Dimensions [mm]					Bit	Cond.
		d	l	dh	lg1	lg2		
DSPROA45.5X50	74287	5.5	50	7	22.5	10.5	T-25	150
DSPROA45.5X60	74288		60	7	27.5	10.5	T-25	150
DSPROA45.5X70	74289		70	7	32.5	10.5	T-25	150
DSPROA45.5X80	74290		80	7	37.5	10.5	T-25	150

Product characteristic properties

Art. nr.	Yield Moment $M_{y,k}$ [Nm]	Withdrawal Parameter $f_{ax,k}$ [N/mm ²]	Head Pull Through Parameter $f_{head,k}$ [N/mm ²]	Characteristic Tensile Capacity $f_{tens,k}$ [kN]
DSPROA45.5X50	7585	12.8	31.8	7.8
DSPROA45.5X60	7585	12.8	31.8	7.8
DSPROA45.5X70	7585	12.8	31.8	7.8
DSPROA45.5X80	7585	12.8	31.8	7.8

DSPROA4
Hardwood Decking Screw - Stainless Steel A4

