

Technický list

SIMPSON**Strong-Tie**

TMC

Metallic Anchor for Plasterboard

The TMC metallic anchor in the versions Ø8, Ø10 and Ø12 mm is designed for fixings on anchoring bases with cavities. The anchor is placed in push-through assembly with the TMC setting tool, tightened and braced against the building material. By means of the pre-mounted metric screws, attachments can then be connected and also removed again in a force-locking manner.

Features

Material

- Steel
- White zinc plated

Benefits

- Wide washer to cover possible hole imperfections
- The setting tool prevents over stressing the base material during installation.

Applications

Applications

- Electrical components
- Radiator brackets
- Pipe clips

Suitable for

- Cell like clay brick (partially suitable)
- Hollow dense aggregate block (partially suitable)
- Hollow light aggregate block (partially suitable)
- Plasterboard
- Panels and sheets

**EZ**

INT




TMC

Metallic Anchor for Plasterboard

Technical Data

Product Dimensions



Art. nr.	Product Reference	Screw Dimensions [dxL _v] [mm]	Hole diameter [d _o] [mm]	Min. wall thickness [h _{min}] [mm]	Max. wall thickness [h _{max}] [mm]	Qty per box	Qty per outer box
7500100403800	TMC	M4x41	8	4	9	100	2000
7500100404500		M4x47	8	9	16	100	2000
7500100504500		M5x43	10	5	13	50	1000
7500100505800		M5x60	10	5	18	50	1000
7500100507100		M5x74	10	18	32	50	1000
7500100604500		M6x45	12	5	12	50	1000
7500100605800		M6x60	12	5	18	50	1000
7500100607100		M6x74	12	18	32	50	1000

Setting Tool



Art. nr.	Product Reference	Qty per box
4990100000100	TMC-MTZ	1

TMC Metallic Anchor for Plasterboard

Installation

