


TML

Nylon plug for aerated concrete

TML concrete anchors Ø10 - Ø 14 mm are specially designed for fastening in aerated concrete. The anchor is placed after pre-drilling, whereby the external thread cuts positively into the building material and ensures a secure hold. The add-on parts can then be mounted using wood screws or metric screws.



Applications

Material

Nylon dowel (polyamide PA6)

Benefits

- High quality nylon plug
- Suitable for wood screws and metric screws

Applications

- Pictures, Lamps
- Cable and pipe clamps
- Wall cupboards, shelves
- Signs
- Letterboxes

Technický list


SIMPSON**Strong-Tie**

TML

Nylon plug for aerated concrete

Technical Data

Dimensions



Art. nr.	Product Reference	Hole Diameter x Length [d _o xL] [mm]	Minimum hole depth [h1] [mm]	Nominal embedment depth [h _{nom}] [mm]	Minimum support thickness [h _{min}] [mm]	Screw diameter min. [mm]	Screw diameter max. [mm]	Metric screw diameter	Anchor length [Lu] [mm]	Qty per box	Qty per outer box
6260100605000	TML	10x50	60	50	75	5.5	6	M6	40	25	250
6260100806000		12x60	70	60	85	7	8	M8	50	25	250
6260101007000		14x70	80	70	100	9	10	M10	60	25	250





Screw Length: $L_v = L_u + t_{fix}$

TML
Nylon plug for aerated concrete

Installation

Suitable for

Aerated concrete



TML
Nylon plug for aerated concrete

