

## Technický list

**SIMPSON**

**Strong-Tie**

BTFFLEX

### Hinge concealed beam hanger

The BTFFLEX can be dowelled into the concrete as a flexible connection, slotted into the timber at the factory and then simply pushed in, secured with the split pin and the next connection can be made.

This solution is particularly flexible if there are different angles between the wooden beam and the wall.

## Features

### Material

**Steel:**

**S235JR acc. to EN10025**

**Coating :**

**Electroplating yellow zinc > 8 µm**

### Benefits

- The variety of connection options are given in the ETA 07/0245, here you will find also information of:
- different slopes
- connections of concrete

## Applications

### Suitable On

**Supporting member:**

- concrete, steel

**Supported member:**

- solid wood, engineered wood



BTFLEX

**Hinge concealed beam hanger**

## Technical Data

Product dimensions




Table "Product dimensions" cannot be displayed : no references available.

Product characteristic capacities - Timber beam to rigid support




Table "Product characteristic capacities - Timber beam to rigid support" cannot be displayed : no references available.

BTFLEX

**Hinge concealed beam hanger**

## Installation

### Fixing

**The following fasteners need to be used:**

- steel dowels Ø12 mm, length acc. width of the joist
- bolts M12 acc. static requirements

BTFLEX

**Hinge concealed beam hanger**