

LTSFR

Skirting skrue rustfri hærdet

*Used outdoor when laying solid wood flooring.
The small screw head means that countersinking
in the base material is improved, and the screw's
design helps preventing wooden floors creaking.
Corrosion resistance of the steel is comparable
with traditional.*



Egenskaber

Material

*

Advantages

- 6 lobe drive
- Trim pan head
- Type 17 point
- Coarse thread with reverse thread

Anvendelse

Support

- Fodpaneler til træ
- Sokkel til stål
- Massivt trægulv til træ

Intend Use


*

LTSFR

Skirting skrue rustfri hærdet

Teknisk data

Product dimensions



Art. nr.	Item code	DB nr.	NOBB nr.	Fastener dimensions [mm]										Qty/box	Vægt [kg]
				d	l	d _h	d ₁	A _h	h _t	l _g	l _p	t _{fix}	bit		
LTSFR3.9X35	75514	2055869	55841743	3.9	35	5	2.2	-	-	23	-	12	TX10	250	0.002
LTSFR3.9X42	75515	2055870	55841758		42	5	2.2	-	-	27	-	15	TX10	250	0.002
LTSFR3.9X57	75516	2055871	55841762		57	5	2.2	-	-	37	-	20	TX10	250	0.002
LTSFR4.5X70	75517	2055872	55841777	4.5	70	5	2.8	-	-	46	-	24	TX15	250	0.004
LTSFR4.5X80	75518	2055873	55841781		80	5	2.8	-	-	50	-	30	TX15	250	0.005

Simpson Strong-Tie A/S
Egeskovvej 33 8700 Horsens
tel: +45 8781 7400
info@strongtie.dk

LTSFR
Skirting skrue rustfri hærdet

