

TS

Wood Fibre to Steel Screw

Used indoors for fixing mouldings, OSB, chipboard and plywood. The wood fiberboard screw has ribs under its head for effective anchoring in the base material, and twin thread for fast speed. Can be used for steel substrates up to 1.0 in thickness.

Egenskaber

Material

Galvaniseret gul zinkstål

Features

- PH-skrue
- Forsænket hoved med ribber
- Skarp spids
- Dobbelt gevind
- Gul zinkbelagt

Anvendelse

Suitable for

- Wood fibre board to steel

When to use


.



TS
Wood Fibre to Steel Screw

Teknisk data

Product dimensions



Art. nr.	Item code	DB nr.	NOBB nr.	Fastener dimensions [mm]										Qty/box	Vægt [kg]
				d	l	d _h	d ₁	A _h	h _t	l _g	l _p	t _{fix}	bit		
TS3.9X28	75495	2055850	55840574	3.9	28	6.8	-	-	-	-	-	-	-	500	0.002
TS3.9X42	75496	2055851	55840585		42	6.8	-	-	-	-	-	-	-	500	0.003
TS3.9X57	75497	2055852	55840593		57	6.8	-	-	-	-	-	-	-	250	0.003

Simpson Strong-Tie A/S
Egeskovvej 33 8700 Horsens
tel: +45 8781 7400
info@strongtie.dk

TS
Wood Fibre to Steel Screw

