

RNTG

**Tagsøm, snoet - Varmgalvaniseret**

*Roofing nail, twisted shank and bell head, which can withstand rain. Has a number of uses, including the installation of constructional and roofing sheeting to a wood base.*

## Egenskaber

### Features:

- Snoet skaft
- Klokkeformet hoved
- Varmgalvaniseret

## Anvendelse


### Application:

- Steel to wood



RNTG

Tagsøm, snoet - Varmgalvaniseret



## Teknisk data

Product dimensions

Art. nr.	Item code	DB nr.	NOBB nr.	Fastener dimensions [mm]										Qty/box	Vægt [kg]
				d	l	d <sub>h</sub>	d <sub>1</sub>	A <sub>h</sub>	h <sub>t</sub>	l <sub>g</sub>	l <sub>p</sub>	t <sub>fix</sub>	bit		
RNTG3.4x75	75671	2056024	55842004	3.4	75	18	-	254.5	4	-	5.1	-	-	75	0.011
RNTG3.4x90	75670	2056023	55837392		90	18	-	254.5	4	-	5.1	-	-	75	0.012

Product characteristic properties

Art. nr.	Product characteristic properties					
	Characteristic Yield Moment – M <sub>y,k</sub> [M <sub>y,k</sub> ] [Nm]	Characteristic withdrawal parameter - f <sub>ax,k,90°</sub> [f <sub>ax,k,90°</sub> ] [N/mm <sup>2</sup> ]	Characteristic head pull-through parameter - f <sub>head,k</sub> [f <sub>head,k</sub> ] [N/mm <sup>2</sup> ]	Characteristic tensile capacity - f <sub>tens,k</sub> [f <sub>tens,k</sub> ] [kN]	Characteristic torsional strength - f <sub>tor,k</sub> [f <sub>tor,k</sub> ] [Nm]	Torsional ratio
RNTG3.4x75	6.1	6.6	12.6	4.6	-	-
RNTG3.4x90	6.1	6.6	12.6	4.6	-	-

