

RNWGC

Ringformet skaft tagsøm med skive, malet RAL 9005

Roofing nail, twisted shank and bell head, which can withstand rain. Has a number of uses, including the installation of constructional and roofing sheeting to a wood base.

Egenskaber

Features:

- Snoet skaft
- Klokkeformet hoved
- Varmgalvaniseret
- Lakeret RAL9005

Anvendelse

Application:


- Steel to wood



RNWGC
Ringformet skaft tagsøm med skive, malet RAL 9005

Teknisk data

Product dimensions



Art. nr.	Item code	DB nr.	NOBB nr.	Fastener dimensions [mm]										Qty/box	Qty/Blister	Vægt [kg]	
				d	l	d _h	d ₁	A _h	h _t	l _g	l _p	t _{fix}	bit				
RNWGC3.7x60	75674	2056027	55839503	3.7	60	18	-	254.5	-	-	-	-	-	-	75	-	0.01
RNWGC3.7X60 Blister	78260	-	-		60	18	-	254.5	-	-	-	-	-	-	-	6	0.009
RNWGC3.7x70	75675	2056028	55842023		70	18	-	254.5	-	-	-	-	-	-	75	-	0.01
RNWGC4.0x95	75676	2056029	55842038	4	95	18	-	254.5	-	-	-	-	-	50	-	0.015	
RNWGC4.0x110	75677	2056030	55842042		110	18	-	254.5	-	-	-	-	-	50	-	0.017	

Product characteristic properties

Art. nr.	Product characteristic properties					
	Characteristic Yield Moment – M _{y,k} [M _{y,k}] [Nm]	Characteristic withdrawal parameter - f _{ax,k,90°} [f _{ax,k,90°}] [N/mm ²]	Characteristic head pull-through parameter - f _{head,k} [f _{head,k}] [N/mm ²]	Characteristic tensile capacity - f _{tens,k} [f _{tens,k}] [kN]	Characteristic torsional strength - f _{tor,k} [f _{tor,k}] [Nm]	Torsional ratio
RNWGC3.7x60	5.5	7.6	13.5	5.7	-	-
RNWGC3.7X60 Blister	5.5	7.6	13.5	5.7	-	-
RNWGC3.7x70	5.5	7.6	13.5	5.7	-	-
RNWGC4.0x95	8.2	7.7	13.5	6.1	-	-
RNWGC4.0x110	8.2	7.7	13.5	6.1	-	-

