

RSN21A4

## Ramme-søm 21° Plaststrimmel - Rund hoved, Ring skaft - Rustfri A4

*The framing nail is used for wood to wood constructions. The round head gives a good visual end result and the plastic collation is not sensitive for wetness. The stainless version can be used in severe environments.*

### Egenskaber

#### Material

\*

#### Advantages

- Rundt hoved
- Ringformet skaft øger udtrækningsmodstanden
- Plaststrimmel 21°

#### Anvendelse

#### Support

- Framing wood to wood


#### Intend Use

\*



RSN21A4

**Ramme-søm 21° Plaststrimmel - Rund hoved, Ring skaft - Rustfri A4**



## Teknisk data

### Product dimensions

Art. nr.	Item code	DB nr.	NOBB nr.	Fastener dimensions [mm]										Qty/box	Vægt [kg]
				d	l	d <sub>h</sub>	d <sub>1</sub>	A <sub>h</sub>	h <sub>t</sub>	l <sub>g</sub>	l <sub>p</sub>	t <sub>flx</sub>	bit		
RSN21A42.8X65	75641	2055995	55841940	2.8	63.5	6.2	-	30.2	0.6	50	2.5	42.6	-	500	0.004
RSN21A42.8X75	75642	2055996	55841955		73.5	6.9	-	37.4	0.6	53	2.5	52.6	-	500	0.004
RSN21A43.1X90	75643	2055997	55841966	3.1	88	6.9	-	37.4	0.8	70	4.3	65.2	-	500	0.006

### Product characteristic properties

Art. nr.	Product characteristic properties					
	Characteristic Yield Moment – M <sub>y,k</sub> [M <sub>y,k</sub> ] [Nm]	Characteristic withdrawal parameter - f <sub>ax,k,90°</sub> [f <sub>ax,k,90°</sub> ] [N/mm <sup>2</sup> ]	Characteristic head pull-through parameter - f <sub>head,k</sub> [f <sub>head,k</sub> ] [N/mm <sup>2</sup> ]	Characteristic tensile capacity - f <sub>tens,k</sub> [f <sub>tens,k</sub> ] [kN]	Characteristic torsional strength - f <sub>tor,k</sub> [f <sub>tor,k</sub> ] [Nm]	Torsional ratio
RSN21A42.8X65	3.2	8.9	29.4	3.4	-	-
RSN21A42.8X75	3.2	8.9	29.4	3.4	-	-
RSN21A43.1X90	4.6	8.3	18.1	3.8	-	-

