

RSN17Z

**Ringstiftsøm 17° Plaststrimmel - Rundt hoved**

*The framing nail is used for wood to wood constructions. The round head gives a good visual end result and the plastic collation is not sensitive for wetness.*

## Egenskaber

### Features:

- Rundt hoved
- Ringformet skaft øger udtrækningsmodstanden
- Plaststrimmel 17°

## Anvendelse


### Application:

- Framing wood to wood



RSN17Z

Ringstiftsøm 17° Plaststrimmel - Rundt hoved



## Teknisk data

## Product dimensions

| Art. nr.     | Item code | DB nr.  | NOBB nr. | Fastener dimensions [mm] |      |                |                |                |                |                |                |                  |     |     | Qty/box | Vægt [kg] |
|--------------|-----------|---------|----------|--------------------------|------|----------------|----------------|----------------|----------------|----------------|----------------|------------------|-----|-----|---------|-----------|
|              |           |         |          | d                        | l    | d <sub>h</sub> | d <sub>1</sub> | A <sub>h</sub> | h <sub>t</sub> | l <sub>g</sub> | l <sub>p</sub> | t <sub>fix</sub> | bit |     |         |           |
| RSN17Z3.1x65 | 75682     | 2056035 | 55842076 | 3.1                      | 64.5 | 6.9            | -              | 37.4           | 0.8            | 41             | 4.3            | 40.2             | -   | 500 | 0.004   |           |

## Product characteristic properties

| Art. nr.     | Product characteristic properties  |  |   |  |   |                 |
|--------------|--|--|---|--|---|-----------------|
|              | Characteristic Yield Moment – M <sub>y,k</sub><br>[M <sub>y,k</sub> ] [Nm] | Characteristic withdrawal parameter - f <sub>ax,k,90°</sub><br>[f <sub>ax,k,90°</sub> ] [N/mm <sup>2</sup> ] | Characteristic head pull-through parameter - f <sub>head,k</sub><br>[f <sub>head,k</sub> ] [N/mm <sup>2</sup> ] | Characteristic tensile capacity - f <sub>tens,k</sub><br>[f <sub>tens,k</sub> ] [kN] | Characteristic torsional strength - f <sub>tor,k</sub> [f <sub>tor,k</sub> ] [Nm] | Torsional ratio |
| RSN17Z3.1x65 | 4.6  | 8.3  | 18.1  | 3.8  | -   | -               |

Simpson Strong-Tie A/S  
Egeskovvej 33 8700 Horsens  
tel: +45 8781 7400  
info@strongtie.dk

RSN17Z  
Ringstiftsøm 17° Plaststrimmel - Rundt hoved

