

## LSF Skirting Screw

*Used indoors for fixing skirting to underlying wood material. The small screw head has ribs on its underside for easy countersinking and a cutpoint to counteract splitting of the woodwork. The screw can also be fixed to a steel base with a maximum thickness of 0.6mm.*

### Egenskaber

#### Material

\*

#### Benefits

- Cylindrisk indstøbningshoved: diskret finish
- Designet giver en perfekt finish og begrænser støj

#### Colors

- 75319 = Gul zink
- 75321 = Gul zink
- 75322 = Gul zink
  
- 75323 = Gul zink + hvidmalet hoved
- 75324 = Gul zink + hvidmalet hoved

### Anvendelse

#### Support

- Fodpaneler til træ
- Sokkel til stål

#### When to use

- Parketlameller af eg eller nåletræ på bjælker
- Træfodlister på metalskinner



LSF  
Skirting Screw

## Teknisk data



Product dimensions

Art. nr.	Item code	DB nr.	NOBB nr.	Fastener dimensions [mm]							Qty/box	Vægt [kg]
				d	l	d <sub>h</sub>	d <sub>1</sub>	l <sub>g</sub>	t <sub>fix</sub>	bit		
LSF3.0X35	75319	2055679	55836143	3	35	5.5	2	23	12	TX10	200	0.002
LSF3.0X42	75321	2055680	55836132		42	5.5	2	27	15	TX10	200	0.002
LSF3.0X57	75322	2055681	55836177		57	5.5	2	37	20	TX10	200	0.003



Lakeret hoved RAL 9010

Art. nr.	Item code	DB nr.	NOBB nr.	Fastener dimensions [mm]							Qty/box
				d	l	d <sub>h</sub>	d <sub>1</sub>	l <sub>g</sub>	t <sub>fix</sub>	bit	
LSF3.0X42 RAL9010	75323	2055682	55836158	3	42	5.5	2	27	15	TX10	200
LSF3.0X57 RAL9010	75324	2055683	55836162		57	5.5	2	37	20	TX10	200

