

VBS

VindueskarmC1:C2102skrue rustfri A4

Painted head to match colored steel plate work for windows. Primarily used for installation of window sills. The window sill screw can deal with aggressive environments. The underside of the head is tapered to ensure a good seal with the sheet or plate. The cutpoint prevents splitting of the frame wood.



Egenskaber

Features:

- Firkantet drev
- Lakeret panhead
- Rustfrit A4


Colors:

- 75520 = Umalet
- 75521 = Hvidmalet hoved
- 75522 = Sortmalet hoved

Anvendelse

Application:

- Vindueskarm til træ
- Metalplade til træ



VBS
VindueskarmC1:C2102skrue rustfri A4


Teknisk data

Product dimensions




Art. nr.	Item code	DB nr.	NOBB nr.	Fastener dimensions [mm]							Qty/box
				d	l	d _h	d ₁	l _g	t _{fix}	bit	
VBS3.5X19	75520	-	55841796	3.5	19	6	2.7	19	0.7	Square	200

Product Dimensions Painted Head RAL 9005



Art. nr.	Item code	NOBB nr.	Fastener dimensions [mm]							Qty/box
			d	l	d _h	d ₁	l _g	t _{fix}	bit	
VBS3.5X19 RAL9005	75522	55841815	3.5	19	6	2.7	19	0.7	Square	200

Product Dimensions Painted Head RAL 9010



Art. nr.	Item code	NOBB nr.	Fastener dimensions [mm]							Qty/box
			d	l	d _h	d ₁	l _g	t _{fix}	bit	
VBS3.5X19 RAL9010	75521	55841800	3.5	19	6	2.7	19	0.7	Square	200

