

BASN17G

Ramme-søm 17° Plaststrimmel - Rund hoved, Takket skaft - HDG

The framing nail is used for wood to wood constructions. The round head gives a good visual end result and the plastic collation is not sensitive for wetness. The barbed shank increases withdrawal resistance.

Egenskaber


Features:

- Rundt hoved
- Takket skaft øger modstandsdygtigheden mod udtrækning
- Plaststrimmel 17°

Anvendelse

Application:

- Framing wood to wood





BASN17G

Ramme-søm 17° Plaststrimmel - Rund hoved, Takket skaft - HDG


Teknisk data

Product Dimensions



Art. nr.	Item code	DB nr.	NOBB nr.	Fastener dimensions [mm]							Qty/box
				d	l	d _h	A _h	h _t	l _p	t _{fix}	
BASN17G2.8X50	75621	2055975	55841425	2.8	49.5	6.6	34.2	1	3.9	32.7	500
BASN17G2.8X55	75622	2055976	55841433		54.5	6.6	34.2	1	3.9	37.7	500
BASN17G2.8X65	75623	2055977	55841444		63.5	6.6	34.2	1	3.9	46.7	500
BASN17G2.8X75	75624 - 75619	2055978 - 2055973	55841452 - 55841917		73.5	6.6	34.2	1	3.9	56.7	500 / 1000
BASN17G3.1X90	75625 - 75620	2055979 - 2055974	55842844 - 55841414	3	88	6.6	34.2	1	4.3	70	500 / 1000

Product characteristic parameters



Art. nr.	Product characteristic properties			
	Characteristic Yield Moment – M _{y,k} [M _{y,k}] [Nm]	Characteristic withdrawal parameter - f _{ax,k,90°} [f _{ax,k,90°}] [N/mm ²]	Characteristic head pull-through parameter - f _{head,k} [f _{head,k}] [N/mm ²]	Characteristic tensile capacity - f _{tens,k} [f _{tens,k}] [kN]
BASN17G2.8X50	2.6	4.9	22.6	4
BASN17G2.8X55	2.6	4.9	22.6	4
BASN17G2.8X65	2.6	4.9	22.6	4
BASN17G2.8X75	2.6	4.9	22.6	4
BASN17G3.1X90	3.9	5.4	20.9	4.8

