

TAN

Selvborende Dybel

TAN nylon dybel er designet til fastgørelse i gipsplader. Skruen kan skrues direkte i et eller to lag gips, uden forboring. Emnet er skal fastgøres monteres med Ø3,0 – Ø4,5 mm træ- gips- eller stålskrue.

Egenskaber

Fordele

- Forboring ikke nødvendig
- Benyttes i vægge af et eller to lag gips

Anvendelse

Materiale

- Nylon

Anvendelsesområder

Trælameller
Gardinskinne
Metalprofiler

Egnet til


Gipsplader



TAN
Selvborende Dybel

Teknisk data

Product Dimensions




Art. nr.	Product Reference	Dimensions [ØxL] [mm]	Plug [Ø x L]	Min. screw diameter [d] [mm]	Max. screw diameter [d] [mm]	Washer diameter d _r [mm]	Min. thread engagement [L _u] [mm]	Qty per box	Qty per outer box	Vægt [kg]
6550501503500	TAN	Ø6.5x35	15x35	3	4.5	14	22	100	1000	0.002

Screw Length: $L_v = L_u + t_{fix}$

Use Phillips PH2 insert with plasterboard plug

Recommended capacities



Art. nr.	Product Reference	Dimensions [ØxL] [mm]	Recommended capacity		Installation data	
			Tension - N _{rec} [kN]		Edge distance [ccr,N] [mm]	Spacing(5) - Scr,N [scr,N] [mm]
			Plasterboard 12,5 mm	Plasterboard 2 x 12,5 mm		
6550501503500	TAN	Ø6.5x35	0.06	0.1	50	50

**These values are for guidance only*

Product Dimension - D.I.Y

Art. nr.	Product Reference	Plug [Ø x L]	Min. screw diameter [d] [mm]	Max. screw diameter [d] [mm]	Pcs/blister	Blister/Pkg.
65505015035F2	TAN	15x35	3	4.5	10	20

TAN Selvborende Dybel

Montering

