

TRZ

Selvborende zamak Dybel

TRZ zamak (zink/aluminium) dybel til fastgørelse i gipsplader, fibergips og gasbeton. Skruen kan skrues direkte i et lag gipsplade. Emnet er skal fastgøres monteres med Ø4,5 mm træ- gips- eller stålskrue.

Egenskaber

Materiale

- zamak (zink/aluminium)

Fordele

- Forboring ikke nødvendig
- Dyblen monteres med akruetrækker

Anvendelse

Anvendelsesområder

- Trælameller
- Gardinskinne
- Metalprofiler

Egnet til


- Gasbeton (AAC)
- Gipsplader

NYHED**YZP**

TRZ
Selvborende zamak Dybel

Teknisk data


Product Dimensions



Art. nr.	Product Reference	Plug diameter x length [ØxL] [mm]	Fixture thickness [t _{fix}] [mm]	Nominal embedment depth* [h _{nom}] [mm]	Min. support thickness* [h _{min}] [mm]	Screw diameter [d] [mm]	Screw length [L _v] [mm]	Washer diameter [d _p] [mm]	Recess	Qty per box	Qty per outer box	Vægt [kg]
7500601303000	TRZ	13x30	10	30	60	4	35	14	PZ2	100	2000	0.007

Values refer to installation on compact base materials such as aerated concrete.

Recommended capacities



Art. nr.	Product Reference	Plug diameter x length [ØxL] [mm]	Recommended capacity				Installation data	
			Tension - N _{rec} [kN]		Shear - V _{rec} [kN]		Characteristic edge distance [ccr,N] [mm]	Characteristic spacing(5) - Scr,N [scr,N] [mm]
			Aerated concrete G4	Plasterboard 12,5 mm	Aerated concrete G4	Plasterboard 12,5 mm		
7500601303000	TRZ	13x30	0.1	0.05	0.2	0.1	50	50

*These values are for guidance only

Product Dimension - D.I.Y

Art. nr.	Product Reference	Plug diameter x length [ØxL] [mm]	Screw diameter [d] [mm]	Screw length [L _v] [mm]	Pcs/blister	Blister/Pkg.
75006013030F2	TRZ	13x30	4	35	5	30

TRZ Selvborende zamak Dybel

Montering

