

CSFT

Skrue med fuldt gevind

CSFT connector screw is designed for steel to wood connections and load rated together with specific Simpson Strong-Tie connectors. The new head shape ensure a good fit in the connector and the full thread increase the load bearing capacity. The flat head makes it possible to get a flush surface after installation.

Egenskaber

Features

- CE-mærket (EN14592)
- Fuldt gevind
- Zinkflakbelægning
- 6-lobe-drev
- Speciel hovedform designet til SST-konnektorer

Material

-


Anvendelse

Brug ved

-

Suitable for

- Wood to wood




CSFT
Skrue med fuldt gevind

Teknisk data



Product Dimensions

Art. nr.	Item code	Fastener dimensions [mm]						Qty per box	Vægt [kg]
		d	l	d _h	d ₁	l _g	bit		
CSFT5.0X70	77308	5	70	8.5	3.5	65	T-20	100	0.006
CSFT6.0X85	77309	6	85	9.5	4	79	T-25	100	0.01
CSFT6.0X110	77310	6	110	9.5	4	103	T-25	100	0.013



Characteristic properties

Art. nr.	Product characteristic properties			
	Characteristic Yield Moment – M _{y,k} [Nm]	Characteristic withdrawal parameter - f _{ax,k,90°} [N/mm ²]	Characteristic tensile capacity - f _{tens,k} [kN]	Torsional ratio
CSFT5.0X70	7.7	17.8	10.7	>1,5
CSFT6.0X85	10.5	13.6	12.9	>1,5
CSFT6.0X110	10.5	13.6	12.9	>1,5

