

FM-MP3 evo SAFER

Anclaje metálico anti-intrusión

El anclaje metálico FM-MP3 evo SAFER es una solución para la fijación anti-intrusión de rejillas, barandillas o puertas.

Características

Materia

- acero electrocincado

Ventajas

- Cuerpo monobloque, con un exclusivo sistema de sujeción del cono
- Instalación sencilla y segura gracias a la cabeza especial: con la parte hexagonal se destaca cuando se llega al par de montaje.

Aplicaciones

Aplicación

- Rejillas para puertas o ventanas
- Puertas
- Estructuras metálicas diversas

Soportes


- Hormigón no fisurado
- Piedra
- Ladrillo macizo
- Ladrillo alveolar (compatibilidad por verificar)

NUEVO**EZ****INTERIOR**

FM-MP3 evo SAFER
Anclaje metálico anti-intrusión

Datos técnicos





Dimensiones



Modelo	Product Reference	Dimensiones [ØxL] [mm]	Esp. piza a fijar [tfix] [mm]	Ø agujeros [mm]	Profundidad mínima de perforación [h1] [mm]	Profundidad nominal de anclaje [hnom]. [mm]	Profundidad de anclaje [hef] [mm]	Ø máx. de perforación pieza a fijar [df]. [mm]	Espesor mín. del soporte [hmin]. [mm]	Cap diameter [ØA] [mm]	Ctd por caja	Ctd por embalaj
73313B1207500	FM-MP3 evo SAFER	M8x75	30	12	70	50	43	13	100	17	50	250

FM-MP3 evo SAFER Anclaje metálico anti-intrusión

Instalación



Installation data

Modelo	Product Reference	Dimensiones [ØxL] [mm]	Ø drilling hole [d0] [mm]	Min. drill depth [h1] [mm]	Ø drilling fixture [df] [mm]	Wrench size [SW] [mm]	Embedment depth [hef] [mm]	Min. support thickness [hmin] [mm]
73313B1207500	FM-MP3 evo SAFER	M8x75	12	70	13	17	43	100

Spacings and edge distances

Modelo	Product Reference	Dimensiones [ØxL] [mm]	Min. edge distance [cmin] [mm]	Min. spacing [smin] [mm]	Characteristic edge distance [ccr,N] [mm]	Characteristic spacing(5) - Scr,N [scr,N] [mm]
73313B1207500	FM-MP3 evo SAFER	M8x75	45	45	65	130

