

GT Drywall to Wood Screw

GT drywall to wood screws are used indoors for fixing drywall boards to wood battens. The duplex head prevents the paper on the plasterboard from tearing when fastening.

Ominaisuuudet

Material

.

Features

- PH drive
- Duplex head
- Sharp point
- Coarse thread
- Electro galvanised coating

Sovellus

Suitable for

- Drywall to wood

When to use

.





GT

Drywall to Wood Screw

Technical Data

Mitat



Tuotenro	Tuotenumero	Mitat [mm]					Paino [kg]
		d	l	d _h	l _g	Bit	
GT3.9X30	75334	3.9	30	8	25.5	PH2	0.002
GT3.9X30 Bulk	74349		30	8	25.5	PH2	0.002
GT3.9X30 Bulk XL	75332		30	8	25.5	PH2	0.002
GT3.9X40	75335		40	8	25.5	PH2	0.002
GT3.9X40 Bulk	74351		40	8	25.5	PH2	0.003
GT3.9X40 Bulk XL	75333		40	8	25.5	PH2	0.003
GT3.9X55	74367		55	8	50.5	PH2	0.003
GT3.9X75	74368		75	8	50	PH2	0.004

GT Collated Screws

Tuotenro	Tuotenumero	DB nr.	NOBB nr.	Mitat [mm]						Qty/box
				d	l	d _h	d ₁	l _g	Bit	
GT3.9X30 Collated	74347	1949863	53292453	3.9	30	8	2.7	25.5	PH2	1000
GT3.9X40 Collated	74348	1949864	53292464	3.9	40	8	2.7	25.5	PH2	1000

* Flat tape collated for standard auto-feed screwdrivers

