

UGTS

Exterior-Drywall to Steel or Wood Screw

UGTS screws are used for fixing exterior sheathing to wood battens and steel joists of 1.0 mm maximum thickness. The head is designed to meet the requirements of fitting exterior drywall boards.

Ominaisuuudet

Features

- Cross point drive.
- Extended bugle head.
- Sharp point.
- High-low thread.
- Protec coating.

Sovellus

Liitos

- Exterior drywall and wind board to wood.
- Exterior drywall and wind board to steel.



Tekniset tiedot



SIMPSON**Strong-Tie®**

UGTS

Exterior-Drywall to Steel or Wood Screw

Technical Data

Mitat



Tuotenro	Tuotenumero	Mitat [mm]				Paino [kg]
		d	l	d _h	Bit	
UGTS3.9X30	74307	3.9	30	8.9	PH2	0.001

UGTS Collated Screws

Tuotenro	Tuotenumero	DB nr.	NOBB nr.	Mitat [mm]				Qty/box
				d	l	d _h	Bit	
UGTS3.9X30 Collated	74305	1949834	53292604	3.9	30	8.9	PH2	1000

* Flat tape collated for standard auto-feed screwdrivers

Simpson Strong-Tie / Gbo Fastening Systems
AB
Bruksvägen 2, 593 75 Gunnebo
tel: 0490-300 00
fax : 0490-233 00

Copyright by Simpson Strong-Tie®

Tämän materiaalin tiedot ovat yksinomaan Simpson Strong-Tie:n © omaisuutta

Tiedot ovat voimassa ja käytettävissä ainoastaan Simpson –Strong-Tie:n © tuotteita käytettäessä.

UGTS

**Exterior-Drywall to Steel or Wood
Screw**

2025-08-23

www.strongtie.fi**SIMPSON****Strong-Tie®**