

Tekniset tiedot

MKSA4 Ring Shank Brick/Wood to Wood Nail

SIMPSON**Strong-Tie®**

This ring shank nail in stainless steel can withstand rain and aggressive environments. Used where high withdrawal strength is required. A common use is in the construction of jetties, thanks to the nail's corrosion resistance. When laying a brick facade the joins are anchored to an existing cross-wall up to 6 m.

Ominaisuudet

Material

-

Advantages

-

Sovellus

Use for

-

Suitable on

-




MKSA4

Ring Shank Brick/Wood to Wood Nail

Technical Data

Mitat



Tuotenro	Tuotenumero	Mitat [mm]				Paino [kg]
		d	l	d _h	l _g	
MKSA44.0X100	74229	4	100	8.5	50	0.011
MKSA44.0X125	74230		125	8.5	50	0.013

Tuotteen ominaisuudet

Tuotenro	Tuotteen ominaisuudet			
	Taivutuslujuus - M _{y,k} [M _{y,k}] [Nmm]	Tyypillinen vetoparametri - f _{ax,k,90°} [f _{ax,k,90°}] [N/mm ²]	Tyypillinen läpivetoparametri - f _{head,k} [f _{head,k}] [N/mm ²]	Tyypillinen vetolujuus - f _{tens,k} [f _{tens,k}] [kN]
MKSA44.0X100	7825	6.2	-	8.3
MKSA44.0X125	7825	6.2	-	8.3

Refer to relevant ITTR or ETA for more details

