

TTUFS Countersunk Wood Screw - Electro Galvanised

Suitable for interior use, the TTUFS screw has a serrated thread to reduce the resistance when driving. It has a type 17 point which prevents wood splitting. 80 mm or longer variants have an additional milling thread to further reduce the resistance.

Ominaisuudet

Features

- 6 lobe drive
- Prismatic countersunk head design ensures a flush finish
- Type 17 point
- Serrated thread
- Electro galvanised

Sovellus

Use on

-






TTUFS
Countersunk Wood Screw - Electro Galvanised

SIMPSON

Strong-Tie®

TTUFS
Countersunk Wood Screw - Electro Galvanised

 Mitat ja
 ominaisarvot


Tuotenro	Item Nr.	Mitat [mm]					Paino [kg]
		d	l	d _h	l _g	Bit	
TTUFS3.0X16	74414	3	16	6	11	T-10	0.001
TTUFS3.0X20	74415		20	6	15	T-10	0.001
TTUFS3.0X25	74416		25	6	20	T-10	0.001
TTUFS3.0X30	74417		30	6	25	T-10	0.001
TTUFS3.0x40	77606		40	6	-	T-10	0.001
TTUFS3.5X16	74418	3.5	16	7	11	T-15	0.001
TTUFS3.5X20	74419		20	7	15	T-15	0.001
TTUFS3.5X25	74420		25	7	20	T-15	0.001
TTUFS3.5X30	74421		30	7	25	T-15	0.001
TTUFS3.5X35	74422		35	7	30	T-15	0.002
TTUFS3.5X40	74423		40	7	35	T-15	0.002
TTUFS3.5X50 PT	74424		50	7	30	T-15	0.002
TTUFS3.5X50 FT	77609		50	7	45	T-15	0.002
TTUFS4.0X20	74425	4	20	8	15	T-20	0.001
TTUFS4.0X25	74426		25	8	20	T-20	0.002
TTUFS4.0X30 PT	77610		25	8	18	T-20	0.002
TTUFS4.0X30 FT	74427		30	8	25	T-20	0.002
TTUFS4.0X35	74428		35	8	30	T-20	0.002
TTUFS4.0X40 PT	77612		40	8	20	T-20	0.002
TTUFS4.0X40 FT	74429		40	8	35	T-20	0.002
TTUFS4.0X45 PT	74430		45	8	29	T-20	0.002
TTUFS4.0X45 FT	77613		45	8	40	T-20	0.002
TTUFS4.0X50 PT	74431		50	8	30	T-20	0.003
TTUFS4.0X50 FT	77615		50	8	45	T-20	0.003
TTUFS4.0X60 PT	74432		60	8	35	T-20	0.003
TTUFS4.0X60 FT	77616		60	8	55	T-20	0.003
TTUFS4.0X70	74433		70	8	40	T-20	0.004
TTUFS4.5X25	74434	4.5	25	8.4	20	T-20	0.002
TTUFS4.5X30	74435		30	8.4	25	T-20	0.002
TTUFS4.5X35 PT	77617		35	8.4	21	T-20	0.002
TTUFS4.5X35 FT	74436		35	8.4	30	T-20	0.002
TTUFS4.5X40 PT	77618		40	8.4	20	T-20	0.003
TTUFS4.5X40 FT	74437		40	8.4	35	T-20	0.003
TTUFS4.5X45 PT	74438		45	8.4	29	T-20	0.003
TTUFS4.5X45 FT	77619		45	8.4	40	T-20	0.003
TTUFS4.5X50 PT	74439		50	8.4	30	T-20	0.003
TTUFS4.5X50 FT	77620		50	8.4	45	T-20	0.003

Diameters 3.0, 3.5 and 4.0 screws are not CE marked.

TTUFS
Countersunk Wood Screw - Electro Galvanised

Tuotenro	Item Nr.	d	Mitat [mm]				Paino [kg]
			l	d _h	l _g	Bit	
TTUFS4.5X60 PT	74440	5	60	8.4	35	T-20	0.004
TTUFS4.5X60 FT	77627		60	8.4	55	T-20	0.004
TTUFS4.5X70	74441		70	8.4	40	T-20	0.005
TTUFS4.5X80	74442		80	8.4	50	T-20	0.005
TTUFS5.0X30	74373		30	9.5	25	T-25	0.003
TTUFS5.0x35	77629		35	9.5	30	T-25	0.003
TTUFS5.0X40 PT	77630		40	9.5	20	T-25	0.003
TTUFS5.0X40 FT	74374		40	9.5	35	T-25	0.003
TTUFS5.0x45	77631		45	9.5	40	T-25	0.003
TTUFS5.0X50 PT	74375		50	9.5	30	T-25	0.004
TTUFS5.0X50 FT	77634		50	9.5	45	T-25	0.004
TTUFS5.0X60 PT	74376		60	9.5	35	T-25	0.005
TTUFS5.0X60 FT	77635		60	9.5	55	T-25	0.005
TTUFS5.0X70	74377		70	9.5	40	T-25	0.006
TTUFS5.0X80	74378		80	9.5	40	T-25	0.006
TTUFS5.0X90	74379		90	9.5	45	T-25	0.007
TTUFS5.0X90 Bulk	75500		90	9.5	45	T-25	-
TTUFS5.0X100	74443		100	9.5	60	T-25	0.008
TTUFS5.0X120	74372		120	9.5	60	T-25	0.009
TTUFS6.0x30	77636	6	30	11.6	24	T-30	0.005
TTUFS6.0X40	74455		40	11.6	34	T-30	0.005
TTUFS6.0X50	74457		50	11.6	30	T-30	0.006
TTUFS6.0X50 FT	77637		50	11.6	44	T-30	0.006
TTUFS6.0X60	74458		60	11.6	35	T-30	0.007
TTUFS6.0X60 FT	77638		60	11.6	54	T-30	0.007
TTUFS6.0X70	74459		70	11.6	40	T-30	0.008
TTUFS6.0X80	74460		80	11.6	40	T-30	0.01
TTUFS6.0X90	74461		90	11.6	45	T-30	0.011
TTUFS6.0X100	74380		100	11.6	60	T-30	0.012
TTUFS6.0X120	74451		120	11.6	70	T-30	0.015
TTUFS6.0X140	74452		140	11.6	70	T-30	0.016
TTUFS6.0X160	74453		160	11.6	70	T-30	0.018
TTUFS6.0X180	74454		180	11.6	70	T-30	0.021

Diameters 3.0, 3.5 and 4.0 screws are not CE marked.

TTUFS

Countersunk Wood Screw - Electro Galvanised

Tuotteen ominaisuudet

Tuotenro	Taivutuslujuus - $M_{y,k}$ [Nmm]	Tyypillinen vetoparametri - $f_{ax,k,90^\circ}$ [N/mm ²]	Tyypillinen läpivetoparametri - $f_{head,k}$ [N/mm ²]	Tyypillinen vetolujuus - $f_{tens,k}$ [kN]
TTUFS4.5X25	4660	14.7	15.6	7.8
TTUFS4.5X30	4660	14.7	15.6	7.8
TTUFS4.5X35 PT	4660	14.7	15.6	7.8
TTUFS4.5X35 FT	4660	14.7	15.6	7.8
TTUFS4.5X40 PT	4660	14.7	15.6	7.8
TTUFS4.5X40 FT	4660	14.7	15.6	7.8
TTUFS4.5X45 PT	4660	14.7	15.6	7.8
TTUFS4.5X45 FT	4660	14.7	15.6	7.8
TTUFS4.5X50 PT	4660	14.7	15.6	7.8
TTUFS4.5X50 FT	4660	14.7	15.6	7.8
TTUFS4.5X60 PT	4660	14.7	15.6	7.8
TTUFS4.5X60 FT	4660	14.7	15.6	7.8
TTUFS4.5X70	4660	14.7	15.6	7.8
TTUFS4.5X80	4660	14.7	15.6	7.8
TTUFS5.0X30	6720	15	17.1	7.9
TTUFS5.0x35	6720	15	17.1	7.9
TTUFS5.0X40 PT	6720	15	17.1	7.9
TTUFS5.0X40 FT	6720	15	17.1	7.9
TTUFS5.0x45	6720	15	17.1	7.9
TTUFS5.0X50 PT	6720	15	17.1	7.9
TTUFS5.0X50 FT	6720	15	17.1	7.9
TTUFS5.0X60 PT	6720	15	17.1	7.9
TTUFS5.0X60 FT	6720	15	17.1	7.9
TTUFS5.0X70	6720	15	17.1	7.9
TTUFS5.0X80	6720	15	17.1	7.9
TTUFS5.0X90	6720	15	17.1	7.9
TTUFS5.0X90 Bulk	6720	15	17.1	7.9
TTUFS5.0X100	6720	15	17.1	7.9
TTUFS5.0X120	6720	15	17.1	7.9
TTUFS6.0x30	9500	12.5	16.6	11.1
TTUFS6.0X40	9500	12.5	16.6	11.1
TTUFS6.0X50	9500	12.5	16.6	11.1
TTUFS6.0X50 FT	9500	12.5	16.6	11.1
TTUFS6.0X60	9500	12.5	16.6	11.1
TTUFS6.0X60 FT	9500	12.5	16.6	11.1
TTUFS6.0X70	9500	12.5	16.6	11.1
TTUFS6.0X80	9500	12.5	16.6	11.1
TTUFS6.0X90	9500	12.5	16.6	11.1
TTUFS6.0X100	9500	12.5	16.6	11.1
TTUFS6.0X120	9500	12.5	16.6	11.1

Refer to relevant ITTR or ETA for more details

TTUFS

Countersunk Wood Screw - Electro Galvanised

Tuotenro	Taivutuslujuus - $M_{y,k}$ [Nmm]	Tyypillinen vetoparametri - $f_{ax,k,90^\circ}$ [N/mm ²]	Tyypillinen läpivetoparametri - $f_{head,k}$ [N/mm ²]	Tyypillinen vetolujuus - $f_{tens,k}$ [kN]
TTUFS6.0X140	9500	12.5	16.6	11.1
TTUFS6.0X160	9500	12.5	16.6	11.1
TTUFS6.0X180	9500	12.5	16.6	11.1

Refer to relevant ITTR or ETA for more details

