

Tekniset tiedot

TTSFS Countersunk Wood Screw - Stainless Steel A4

SIMPSON**Strong-Tie**

Suitable for exterior use, the TTSFS screw has a serrated thread to reduce the resistance when driving. It has a type 17 point which prevents wood splitting. 80 mm or longer variants have an additional milling thread to further reduce the resistance.

Ominaisuudet

Features

- 6 lobe drive.
- Flat head with facet.
- Type 17 point.
- Coarse, serrated thread.
- Stainless steel.

Sovellus

Liitos

- Puu-puu liitos





TTSFS

Countersunk Wood Screw - Stainless Steel A4

Technical Data

Mitat ja ominaisarvot



Tuotenro	Tuotenumero	Mitat [mm]						Paino [kg]
		d	l	d _h	l _g	t _{fix}	Bit	
TTSFS5.0X60	74446	5	60	9.5	32	28	T-25	0.005
TTSFS5.0X70	74447		70	9.5	35	35	T-25	0.006
TTSFS5.0X80	74448		80	9.5	40	40	T-25	0.006
TTSFS5.0X90	74449		90	9.5	45	45	T-25	0.007
TTSFS5.0X100	74444		100	9.5	55	45	T-25	0.008
TTSFS5.0X120	74445		120	9.5	60	60	T-25	0.01
TTSFS6.0X70	74473	6	70	11.6	35	35	T-30	0.008
TTSFS6.0X80	74474		80	11.6	40	40	T-30	0.01
TTSFS6.0X90	74475		90	11.6	45	45	T-30	0.011
TTSFS6.0X100	74450		100	11.6	55	45	T-30	0.012
TTSFS6.0X120	74471		120	11.6	60	60	T-30	0.014
TTSFS6.0X140	74472		140	11.6	65	75	T-30	0.016

Tuotteen ominaisuudet

Tuotenro	Taivutuslujuus - $M_{y,k}$ [Nmm]	Tyypillinen vetoparametri - $f_{ax,k,90^\circ}$ [N/mm ²]	Tyypillinen läpivetoparametri - $f_{head,k}$ [N/mm ²]	Tyypillinen vetolujuus - $f_{tens,k}$ [kN]
TTSFS5.0X60	4710	14.9	16	6.3
TTSFS5.0X70	4710	14.9	16	6.3
TTSFS5.0X80	4710	14.9	16	6.3
TTSFS5.0X90	4710	14.9	16	6.3
TTSFS5.0X100	4710	14.9	16	6.3
TTSFS5.0X120	4710	14.9	16	6.3
TTSFS6.0X70	8570	13.6	16.2	9.5
TTSFS6.0X80	8570	13.6	16.2	9.5
TTSFS6.0X90	8570	13.6	16.2	9.5
TTSFS6.0X100	8570	13.6	16.2	9.5
TTSFS6.0X120	8570	13.6	16.2	9.5
TTSFS6.0X140	8570	13.6	16.2	9.5

