

Tekniset tiedot

TTZNFP Pan Head Wood Screw - Impreg®+

SIMPSON
Strong-Tie

Suitable for exterior use, the TTZNFP screw has a serrated thread to reduce the resistance when driving. It has a Type 17 which prevents splitting.

Ominaisuudet


Features

- 6 lobe drive.
- Pan head.
- Type 17 point.
- Serrated thread.
- Impreg®+.

Sovellus

Liitos

- Puu-puu liitos
- Steel to wood





TTZNFP

Pan Head Wood Screw - Impreg®+

Technical Data

Mitat ja ominaisarvot



Tuotenro	Tuotenumero	Mitat [mm]					Paino [kg]
		d	l	d _h	l _g	Bit	
TTZNFP4.0X30*	74537	4	30	8	30	T-20	0.002
TTZNFP4.0X40*	74538		40	8	40	T-20	0.003
TTZNFP4.0X50*	74539		50	8	30	T-20	0.003
TTZNFP5.0X40	74540	5	40	9.7	36	T-25	0.004
TTZNFP5.0X50	74541		50	9.7	30	T-25	0.005
TTZNFP5.0X60	74542		60	9.7	35	T-25	0.006
TTZNFP5.0X70	74543		70	9.7	40	T-25	0.006

* not covered by CE marking

Tuotteen ominaisuudet

Tuotenro	Tuotteen ominaisuudet			
	Taivutuslujuus - M _{y,k} [M _{y,k}] [Nmm]	Tyypillinen vetoparametri - f _{ax,k,90°} [f _{ax,k,90°}] [N/mm ²]	Tyypillinen läpivetoparametri - f _{head,k} [f _{head,k}] [N/mm ²]	Tyypillinen vetolujuus - f _{tens,k} [f _{tens,k}] [kN]
TTZNFP5.0X40	6720	15	16.9	7.9
TTZNFP5.0X50	6720	15	16.9	7.9
TTZNFP5.0X60	6720	15	16.9	7.9
TTZNFP5.0X70	6720	15	16.9	7.9

Refer to relevant ITTR or ETA for more details

