Tekniset tiedot

LTSF
Skirting Screw

The floor/skirting screw is used indoors for fixing skirting or when laying solid wood flooring, such as pine, oak and beech. The small screw head allows countersinking into the base material and the design helps prevent wooden floors creaking. Use with wood or steel maximum 0.6 mm.

Ominaisuudet

Features

- 6 lobe drive
- Trim pan head
- Type 17 point
- Coarse thread with reverse thread

Sovellus

Suitable for

- Skirting to wood
- Skirting to steel
- Solid wood flooring to wood

Technical Data

Mitat

Tuotenro	Tuotenumero	Mitat [mm]					
		d	l	d_h	l_g	$l-l_g$	Bit
LTSF3.9X35	74371	3.9	35	5	23	12	TX10
LTSF3.9X42	74360		42	5	28	14	TX10
LTSF3.9X57	74381		57	5	38	19	TX10
LTSF3.9X70	74382		70	5	46	24	TX10

Painted Head RAL 9010

Tuotenro	Tuotenumero	DB nr.	NOBB nr.	Mitat [mm]							Qty/box
				d	l	d_h	d_1	l_g	$l-l_g$	Bit	
LTSF3.9X42 RAL9010	74383	1949878	53292680	3.9	42	5	2.7	28	14	TX10	250
LTSF3.9X57 RAL9010	74384	1949879	53292695		57	5	2.7	38	19	TX10	250

Simpson Strong-Tie / Gbo Fastening Systems AB
Bruksvägen 2, 593 75 Gunnebo
tel: 0490-300 00
fax : 0490-233 00

Copyright by Simpson Strong-Tie®
Tämän materiaalin tiedot ovat yksinomaan Simpson Strong-Tie:n © omaisuutta
Tiedot ovat voimassa ja käytettävissä ainoastaan Simpson –Strong-Tie:n © tuotteita käytettäessä.

2024-04-23