

DSIX4

Decking Screw - Impreg®X4

The DSIX4 decking screws are designed for treated wood. The screws have a 6 lobe recess to ensure good grip. The type 17 point drives the screw efficiently and prevents wood splitting.

Ominaisuuudet

Features

- 6 lobe drive
- Countersunk with ribs
- Coarse thread
- Type 17 point
- Impreg® X4 coating

Sovellus

Suitable for



- Decking to wood.




DSIX4
Decking Screw - Impreg®X4

Technical Data

Mitat ja ominaisarvot



Tuotenro	Tuotenumero	Mitat [mm]						Paino [kg]
		d	l	d _h	l _g	t _{fix}	Bit	
DSIX44.2X35T-20	74361	4.2	35	7.3	20	15	T-20	0.002
DSIX44.2X45T-20	74362		45	7.3	23.5	21.5	T-20	0.003
DSIX44.2X55T-20	74363		55	7.3	27.5	27.5	T-20	0.003
DSIX44.2X75T-20	74365		75	7.3	40.5	34.5	T-20	0.004



Collated Screws

Tuotenro	Tuotenumero	DB nr.	NOBB nr.	Mitat [mm]							Box Quantity
				d	l	d _h	d ₁	l _g	t _{fix}	Bit	
DSIX44.2X45PH2	74294	-	53293656	4.2	45	7.3	2.5	23.5	21.5	PH2	1000
DSIX44.2X55PH2	74354	1949813	53293660	4.2	55	7.3	2.5	27.5	27.5	PH2	1000
DSIX44.2X75PH2	74355	1949814	53293675	4.2	75	7.3	2.7	40.5	34.5	PH2	400

Tuotteen ominaisuudet

Tuotenro	Taivutuslujuus - M _{y,k} [Nmm]	Tyypillinen vetoparametri - f _{ax,k,90°} [N/mm²]	Tyypillinen läpivetoparametri - f _{head,k} [N/mm²]	Tyypillinen vetolujuus - f _{tens,k} [kN]
DSIX44.2X35T-20	4295	13.9	14.4	6
DSIX44.2X45T-20	4295	13.9	14.4	6
DSIX44.2X55T-20	4295	13.9	14.4	6
DSIX44.2X75T-20	4749	22.9	17.1	6
DSIX44.2X45PH2	4295	13.9	14.4	6
DSIX44.2X55PH2	4295	13.9	14.4	6
DSIX44.2X75PH2	4749	22.9	17.1	6

