

Tekniset tiedot

DSPIX4

Decking Screw Pro - Impreg®X4

SIMPSON

Strong-Tie

The DSIX4 decking screws are designed for treated wood. The screws have a 6 lobe recess to ensure good grip. The type 17 point drives the screw efficiently and prevents wood splitting.

Ominaisuuudet

Features

- 6 Lobe drive
- Cap head
- Coarse thread
- Type 17 point
- Impreg® X4 coating

Sovellus

Suitable for

- Decking boards to wood





DSPIX4

Decking Screw Pro - Impreg®X4

Technical Data

Mitat ja ominaisarvot



Tuotenro	Tuotenumero	NOBB nr.	Mitat [mm]						Paino [kg]
			d	l	d _h	l _{g1}	l _{g2}	Bit	
DSPIX44.8X60	74356	53293705	4.8	60	6.5	26	12	T-20	0.005
DSPIX44.8X70	74357	53293713		70	6.5	32	18	T-20	0.005
DSPIX45.5X80	74358	53293724	5.5	80	7	37.5	20	T-25	0.009
DSPIX46.5X95	74359	53293732	6.5	95	8	40	29	T-30	0.015

Tuotteen ominaisuudet

Tuotenro	Taivutuslujuus - $M_{y,k}$ [Nmm]	Tyypillinen vetoparametri - $f_{ax,k,90^\circ}$ [N/mm ²]	Tyypillinen läpivetoparametri - $f_{head,k}$ [N/mm ²]	Tyypillinen vetolujuus - $f_{tens,k}$ [kN]	Vääntösuhde
DSPIX44.8X60	5951	15.1	32.2	7.9	1.8
DSPIX44.8X70	5951	15.1	32.2	7.9	1.8
DSPIX45.5X80	11193	15.7	33.3	12.2	1.8
DSPIX46.5X95	13203	15.8	45.7	12.9	1.5

