

RST Hard Drywall to Steel Screw

RST screws are used indoors for fixing hard drywall boards to steel joists with a maximum thickness of 1.0 mm. The design of the screw with counter-threads removes enough plaster for the head to become properly countersunk in the board.

Ominaisuuudet

Features

- PH drive
- Reduced bugle head
- Sharp point
- Twin thread with reverse thread
- Phosphated coating

Sovellus

Liitos

- Hard drywall/plasterboard to steel.





RST

Hard Drywall to Steel Screw

Technical Data

Mitat



Tuotenro	Tuotenumero	Mitat [mm]					Paino [kg]
		d	l	d _h	l _g	Bit	
RST3.9X32 Bulk	74318	3.9	32	6.4	22	PH2	0.002
RST3.9X41	74319		41	6.4	31	PH2	0.002
RST3.9X25 Collated	74321		25	6.4	15	PH2	0.001
RST3.9X32 Collated	74322		32	6.4	22	PH2	0.001
RST3.9X41 Collated	74323		41	6.4	31	PH2	0.002
RST4.2X57	74320	4.2	57	6.4	31	PH2	0.002
RST4.2X57 Collated	74324		57	6.4	31	PH2	-

RST Collated Screws

Tuotenro	Tuotenumero	DB nr.	NOBB nr.	Mitat [mm]						Qty/box
				d	l	d _h	d ₁	l _g	Bit	
RST3.9X32 Bulk	74318	1949845	53292725	3.9	32	6.4	2.5	22	PH2	1000
RST3.9X41	74319	1949846	53292733	3.9	41	6.4	2.5	31	PH2	1000
RST4.2X57	74320	1949847	53292744	4.2	57	6.4	2.9	31	PH2	250
RST3.9X25 Collated	74321	1949848	53292752	3.9	25	6.4	2.5	15	PH2	1000
RST3.9X32 Collated	74322	1949849	53292763	3.9	32	6.4	2.5	22	PH2	1000
RST3.9X41 Collated	74323	1949850	53292778	3.9	41	6.4	2.5	31	PH2	1000
RST4.2X57 Collated	74324	1949851	53292782	4.2	57	6.4	2.9	31	PH2	1000

* Flat tape collated for standard auto-feed screwdrivers

