

FARMZC**Steel Roofing and Cladding to Wood Screw**

Farmer screw with drill point is used to fix profiled metal sheet to wood for roof and wall installation. Fit the screw in the concave part of the profiled sheet. Drilling capacity is 2.0 x 1.0 mm.

Ominaisuudet

Features:

- 8 mm Hex head
- Drill point
- Painted head
- EPDM washer
- Electro galvanised 20 µm

Colors:

- 75705 = Black painted head RAL 9005
- 75708 = Black painted head RAL 9005
- 75710 = Black painted head RAL 9005
- 75706 = Red painted head RAL 3009
- 75709 = Red painted head RAL 3009
- 75704 = White painted head RAL 9010
- 75707 = White painted head RAL 9010

Sovellus

Application:

- Steel to wood




FARMZC

Steel Roofing and Cladding to Wood Screw


Technical Data

Product dimensions Painted Head RAL 3009





Tuotenro	Item code	NOBB nr.	Fastener dimensions [mm]							Qty/box
			d	l	d _h	d ₁	l _g	t _{fix}	bit	
FARMZC4.8X20 RAL3009	75706	55836124	4.8	20	14	3.4	17	1	SW8	250
FARMZC4.8X35 RAL3009	75709	55836075		35	14	3.4	32	2	SW8	250

Product dimensions Painted Head RAL 9005



Tuotenro	Item code	NOBB nr.	Fastener dimensions [mm]							Qty/box
			d	l	d _h	d ₁	l _g	t _{fix}	bit	
FARMZC4.8X20 RAL9005	75705	55838258	4.8	20	14	17	1	SW8		
FARMZC4.8X35 RAL9005	75708	21099544		35	14	32	2	SW8		
FARMZC4.8X60 RAL9005	75710	55836060		60	14	57	2	SW8		



Product dimensions Painted Head RAL 9010

Tuotenro	Item code	NOBB nr.	Fastener dimensions [mm]							Qty/box
			d	l	d _h	d ₁	l _g	t _{fix}	bit	
FARMZC4.8X20 RAL9010	75704	55842163	4.8	20	14	3.4	17	1	SW8	250
FARMZC4.8X35 RAL9010	75707	55838232		35	14	3.4	32	2	SW8	250

