

FSA2

Wafer Head Steel or Wood Screw

FSA2 screws are used to fix external board materials such as drywall and fibre cement board to wood battens or steel joists up to 1.0 mm in thickness.

Ominaisuuudet

Benefits

- **Thin flat head: better fixation of the element**
- **Tapered tip: better penetration into the wood**

Sovellus

Support


- Drywall to steel or wood
- Fibre cement to steel or wood



FSA2

Wafer Head Steel or Wood Screw

Technical Data



Product dimensions

Tuotenro	Item code	NOBB nr.	Fastener dimensions [mm]						Paino [kg]
			d	l	d _h	l _g	t _{flx}	bit	
FSA24.2X25	75440	55840521	4.2	25	11.6	25	-	-	0.003
FSA24.2X40	75441	55840536		40	11.6	40	-	-	0.004
FSA24.2X50	75442	55840517		50	11.6	50	-	-	0.005
FSA24.2X60	75443	55840502		60	11.6	40	-	-	0.006

Simpson Strong-Tie / Gbo Fastening Systems AB
Bruksvägen 2, 593 75 Gunnebo
tel: 0490-300 00
fax : 0490-233 00

Copyright by Simpson Strong-Tie®

Tämän materiaalin tiedot ovat yksinomaan Simpson Strong-Tie:n © omaisuutta

Tiedot ovat voimassa ja käytettävissä ainoastaan Simpson –Strong-Tie:n © tuotteita käytettäessä.

FSA2

Wafer Head Steel or Wood Screw

www.strongtie.fi

SIMPSON

Strong-Tie®

2025-08-23