

LBS

Lightweight Concrete Screw

Fasten screw without pre-drilling directly into the porous stone material. Use a low rpm drilling machine but avoid tightening the screw too hard. If this happens the thread loses its grip from the bedding and a new fitting should be done. Minimum anchorage is 60 mm.

Ominaisuudet

Features:

- Protec coating
- Countersunk head with nibs

Sovellus

Application:

- Wood to lightweight concrete




LBS

Lightweight Concrete Screw

Technical Data

Product dimensions



Tuotenro	Item code	NOBB nr.	Fastener dimensions [mm]						Paino [kg]
			d	l	d _h	l _g	t _{fix}	bit	
LBS8.0x65	75259	55840960	8	65	12	60	5	T-30	0.014
LBS8.0x110	75327	55838958	8	110	12	60	50	T-30	0.024
LBS8.0x130	75328	55836476	8	130	12	60	70	T-30	0.03
LBS8.0x180	75329	55836480	8	180	12	60	120	T-30	0.041
LBS8.0x210	75330	55836495	8	210	12	60	150	T-30	0.048

Simpson Strong-Tie / Gbo Fastening Systems AB
Bruksvägen 2, 593 75 Gunnebo
tel: 0490-300 00
fax : 0490-233 00

Copyright by Simpson Strong-Tie®

Tämän materiaalin tiedot ovat yksinomaan Simpson Strong-Tie:n © omaisuutta

Tiedot ovat voimassa ja käytettävissä ainoastaan Simpson Strong-Tie:n © tuotteita käytettäessä.

LBS

Lightweight Concrete Screw

www.strongtie.fi

SIMPSON

Strong-Tie®

2025-08-19