

EKS Express Nail

An express nail used indoors for assembly of wood and steel joists to concrete, stone or other solid building materials.

Ominaisuudet

Features:

- Spring steel
- Electro galvanised

Sovellus

Application:


- Wood to Concrete/stone
- Steel to Concrete/stone

**EG****INDOOR**

EKS
Express Nail

Technical Data

Product dimensions



Tuotenro	Item code	NOBB nr.	Fastener dimensions [mm]						Paino [kg]
			d	l	d _h	l _g	t _{fix}	bit	
EKS6.0x60	75315	55841058	6	60	-	-	30	-	0.007
EKS8.0x70	75316	55841062	8	70	-	-	30	-	0.012
EKS8.0x90	75317	55841077	8	90	-	-	50	-	0.015
EKS8.0x110	75318	55841081	8	110	-	-	70	-	0.019
EKS8.0x130	75314	55841043	8	130	-	-	90	-	0.023

Simpson Strong-Tie / Gbo Fastening Systems AB
Bruksvägen 2, 593 75 Gunnebo
tel: 0490-300 00
fax : 0490-233 00EKS
Express NailCopyright by Simpson Strong-Tie®
Tämän materiaalin tiedot ovat yksinomaan Simpson Strong-Tie:n © omaisuutta
Tiedot ovat voimassa ja käytettävissä ainoastaan Simpson Strong-Tie:n © tuotteita käytettäessä.

2025-08-23



www.strongtie.fi