

Tekniset tiedot

SIMPSON

Strong-Tie

CLNG

Cladding Nail - Hot Dip Galvanised

The CLNG cladding is developed for installing wood cladding. The length of the nail is developed to not penetrate the wind shield/protection behind the facade and the flat head covers the opened wood fibre after insertion. The ring shank increase the withdrawal performance and the 60 degree diamond point prevents splitting.

Ominaisuudet

Features:

- Flat head
- 60 degree diamond point
- Ring shank

Sovellus

Application:

- Cladding to wood
- Facade to wood




CLNG

Cladding Nail - Hot Dip Galvanised

Technical Data

Product dimensions



Tuotenro	Item code	Fastener dimensions [mm]						Paino [kg]
		d	l	d _h	l _g	t _{fix}	bit	
CLNG2.8x65	75649	2.8	63.5	6.9	50	41.1	-	1.8
CLNG2.8x48	75648		47	6.9	24	24.6	-	0.003

Product characteristic properties

Tuotenro	Product characteristic properties					
	Characteristic Yield Moment – M _{y,k} [M _{y,k}] [Nm]	Characteristic withdrawal parameter - f _{ax,k,90°} [f _{ax,k,90°}] [N/mm ²]	Characteristic head pull-through parameter - f _{head,k} [f _{head,k}] [N/mm ²]	Characteristic tensile capacity - f _{tens,k} [f _{tens,k}] [kN]	Characteristic torsional strength - f _{tor,k} [f _{tor,k}] [Nm]	Torsional ratio
CLNG2.8x65	3.2	8.9	29.4	3.4	-	-
CLNG2.8x48	3.2	8.9	29.4	3.4	-	-

