

RNTG

Roofing Nail Twisted - Hot Dip Galvanised

Roofing nail, twisted shank and bell head, which can withstand rain. Has a number of uses, including the installation of constructional and roofing sheeting to a wood base.

Ominaisuuudet

Features:

- Twisted shank
- Bell head
- Hot dip galvanised

Sovellus

Application:

- Steel to wood



RNTG

Roofing Nail Twisted - Hot Dip Galvanised

Technical Data

Product dimensions



Tuotenro	Item code	Fastener dimensions [mm]							Paino [kg]
		d	l	d _h	h _t	l _g	t _{fix}	bit	
RNTG3.4x75	75671	3.4	75	18	4	-	-	-	0.011
RNTG3.4x90	75670		90	18	4	-	-	-	0.012

Product characteristic properties

Tuotenro	Product characteristic properties					
	Characteristic Yield Moment – M _{y,k} [M _{y,k}] [Nm]	Characteristic withdrawal parameter - f _{ax,k,90°} [f _{ax,k,90°}] [N/mm ²]	Characteristic head pull-through parameter - f _{head,k} [f _{head,k}] [N/mm ²]	Characteristic tensile capacity - f _{tens,k} [f _{tens,k}] [kN]	Characteristic torsional strength - f _{tor,k} [f _{tor,k}] [Nm]	Torsional ratio
RNTG3.4x75	6.1	6.6	12.6	4.6	-	-
RNTG3.4x90	6.1	6.6	12.6	4.6	-	-

