

CLNC15G

Cladding Nail 15° Plastic Coil - Round Head, Ring shank - HDG

Cladding nail is mainly used for painted facades. The length of the cladding nail is developed to not penetrate the wind shield/protection behind the facade and the flat head covers the opened wood fibre after insertion. The ring shank increase the withdrawal performance and the 60 degree diamond point prevents splitting.

Ominaisuuudet

Advantages

- Round head
- 60 degree diamond point
- Ring shank
- Plastic coil 15°

Sovellus

Support

- Cladding/facade wood to wood




CLNC15G

Cladding Nail 15° Plastic Coil - Round Head, Ring shank - HDG

Technical Data

Product dimensions



Tuotenro	Item code	NOBB nr.	Fastener dimensions [mm]						Paino [kg]
			d	l	d _h	l _g	t _{fix}	bit	
CLNC15G2.5X65	75739	55837600	2.5	63.5	6.7	50	43.5	-	0.003
CLNC15G2.8X48	75740	55837581	2.8	47	6.9	24	24.6	-	0.002
CLNC15G2.8X65	75741	55837596		63.5	6.9	50	41.1	-	0.004
CLNC15G2.8X75	75742	55837615		73.5	6.9	53	51.1	-	0.005

Product characteristic properties

Tuotenro	Product characteristic properties					
	Characteristic Yield Moment – M _{y,k} [M _{y,k}] [Nm]	Characteristic withdrawal parameter - f _{ax,k,90°} [f _{ax,k,90°}] [N/mm²]	Characteristic head pull-through parameter - f _{head,k} [f _{head,k}] [N/mm²]	Characteristic tensile capacity - f _{tens,k} [f _{tens,k}] [kN]	Characteristic torsional strength - f _{tor,k} [f _{tor,k}] [Nm]	Torsional ratio
CLNC15G2.5X65	2	5.1	22	3	-	-
CLNC15G2.8X48	3.2	8.9	29.4	3.4	-	-
CLNC15G2.8X65	3.2	8.9	29.4	3.4	-	-
CLNC15G2.8X75	3.2	8.9	29.4	3.4	-	-

