

Tekniset tiedot

CLNC15A4

Cladding Nail 15° Plastic Coil - Round Head, Ring shank - Stainless A4

SIMPSON

Strong-Tie

Cladding nail is mainly used for painted facades. The length of the cladding nail is developed to not penetrate the wind shield/protection behind the facade and the flat head covers the opened wood fibre after insertion. The ring shank increase the withdrawal performance and the 60 degree diamond point prevents splitting.

Ominaisuudet

Advantages

- Round head
- 60 degree diamond point
- Ring shank
- Plastic coil 15°

Sovellus

Support


- Cladding/facade wood to wood



CLNC15A4

Cladding Nail 15° Plastic Coil - Round Head, Ring shank - Stainless A4

Technical Data



Product dimensions

Tuotenro	Item code	NOBB nr.	Fastener dimensions [mm]						Paino [kg]
			d	l	d _h	l _g	t _{fix}	bit	
CLNC15A42.8X48	75743	55837626	2.8	47	6.9	26	24.6	-	0.003
CLNC15A42.8X65	75744	55842394		63.5	6.9	50	41.1	-	0.004
CLNC15A42.8X75	75745	55837634		73.5	6.9	53	51.1	-	0.004

Product characteristic properties

Tuotenro	Product characteristic properties					
	Characteristic Yield Moment – M _{y,k} [M _{y,k}] [Nm]	Characteristic withdrawal parameter - f _{ax,k,90°} [f _{ax,k,90°}] [N/mm²]	Characteristic head pull-through parameter - f _{head,k} [f _{head,k}] [N/mm²]	Characteristic tensile capacity - f _{tens,k} [f _{tens,k}] [kN]	Characteristic torsional strength - f _{tor,k} [f _{tor,k}] [Nm]	Torsional ratio
CLNC15A42.8X48	3.2	8.9	29.4	3.4	-	-
CLNC15A42.8X65	3.2	8.9	29.4	3.4	-	-
CLNC15A42.8X75	3.2	8.9	29.4	3.4	-	-

