

Tekniset tiedot

CLN34G

Cladding Nail 34° Paper Tape - Off-set Round Head, Ring shank - HDG

SIMPSON

Strong-Tie

The hot dip galvanised cladding nail is mainly used for painted facades. The length of the nail is developed to not penetrate the wind shield/protection behind the facade and the flat head covers the opened wood fibre after insertion.

The ring shank increase the withdrawal performance and the 60 degree diamond point prevents splitting.

Ominaisuudet

Advantages

- Off-set round head
- 60 Degree diamond point
- Ring shank
- Hot dip galvanised
- Paper tape 34°

Sovellus

Support

- Cladding/facade wood to wood




CLN34G

Cladding Nail 34° Paper Tape - Off-set Round Head, Ring shank - HDG

Technical Data

Product dimensions



Tuotenro	Item code	NOBB nr.	Fastener dimensions [mm]						Paino [kg]
			d	l	d _h	l _g	t _{fix}	bit	
CLN34G2.8X48	75761	55837774	2.8	48	6.5	28	24.6	-	0.002

Product characteristic properties

Tuotenro	Product characteristic properties					
	Characteristic Yield Moment – M _{y,k} [M _{y,k}] [Nm]	Characteristic withdrawal parameter - f _{ax,k,90°} [f _{ax,k,90°}] [N/mm ²]	Characteristic head pull-through parameter - f _{head,k} [f _{head,k}] [N/mm ²]	Characteristic tensile capacity - f _{tens,k} [f _{tens,k}] [kN]	Characteristic torsional strength - f _{tor,k} [f _{tor,k}] [Nm]	Torsional ratio
CLN34G2.8X48	2.5	7.1	12.8	-	-	-

