

SWC

Structural Countersunk Wood Screw

SWC is a countersunk structural screw designed for load-bearing wood structures. The SWC screw has a milling thread to allow for smooth driving of the shank. The countersunk head gives flush fitting while allowing the wood members to close up firmly.

Ominaisuudet

Features:

- No pre-drilling required
- High withdrawal resistance
- Milling thread allows smooth driving
- Countersunk head

Material

Steel - Electrogalvanised yellow zinc coating

Sovellus

Application:

- Wood to wood

advantage

The countersunk head with milling ribs on the underside of the head can be and flush with the surface of the wood, creating a harmonious appearance.

The cutting point design in combination with the reaming shank ensures efficient and smooth screwing with a simultaneous minimization of the insertion resistance and reducing the splitting effect.




SWC

Structural Countersunk Wood Screw

Technical Data

Product dimensions



Tuotenro	Item code	NOBB nr.	Gunnebo art. nr.	Fastener dimensions [mm]						Paino [kg]
				d	l	t _{fix}	d _h	l _g	bit	
SWC6.0X200	75346	55838894	71979	6	200	130	11.8	70	T-30	0.022
SWC6.0X220	75347	55838932	71980		220	150	11.8	70	T-30	0.025
SWC6.0X240	75348	55838913	71991		240	170	11.8	70	T-30	0.027
SWC6.0X260	75349	55838943	71992		260	190	11.8	70	T-30	0.029
SWC6.0X280	75350	55838924	71993		280	190	11.8	70	T-30	0.031
SWC6.0X300	75351	55838905	71994		300	230	11.8	70	T-30	0.033
SWC8.0X80	75352	55836374	76789	8	80	30	14.6	50	T-40	0.018
SWC8.0X100	75353	55836366	71996		100	50	14.6	50	T-40	0.023
SWC8.0X120	75354	55836298	71997		120	40	14.6	80	T-40	0.027
SWC8.0X140	75355	55836385	71998		140	60	14.6	80	T-40	0.031
SWC8.0X160	75356	55836253	71999		160	80	14.6	80	T-40	0.035
SWC8.0X180	75357	55836393	72000		180	100	14.6	80	T-40	0.039
SWC8.0X200	75358	55836321	76781		200	120	14.6	80	T-40	0.043
SWC8.0X220	75359	55836317	76783		220	140	14.6	80	T-40	0.047
SWC8.0X240	75360	55836245	76784		240	160	14.6	80	T-40	0.051
SWC8.0X260	75361	55836340	76785		260	180	14.6	80	T-40	0.055
SWC8.0X280	75362	55836302	76786		280	200	14.6	80	T-40	0.06
SWC8.0X300	75363	55836272	76787		300	220	14.6	80	T-40	0.064
SWC8.0X320	75364	55836336	76788		320	240	14.6	80	T-40	0.068
SWC8.0X340	75365	55836355	72008		340	260	14.6	80	T-40	0.072
SWC8.0X360	75366	55836264	72009		360	280	14.6	80	T-40	0.076
SWC8.0X380	75367	55836283	72010		380	300	14.6	80	T-40	0.08
SWC8.0X400	75368	55836234	72011		400	320	14.6	80	T-40	0.084
SWC10.0X100	76916	60019777	76922	10	100	50	17.8	50	T-40	0.034
SWC10.0X120	76917	60019778	76923		120	70	17.8	50	T-40	0.04
SWC10.0X140	76918	60019779	76924		140	60	17.8	80	T-40	0.046
SWC10.0X160	75369	55838803	76769		160	80	17.8	80	T-40	0.052
SWC10.0X180	75370	55838818	72013		180	100	17.8	80	T-40	0.058
SWC10.0X200	75371	55838822	76770		200	120	17.8	80	T-40	0.064
SWC10.0X220	75372	55838837	76771		220	140	17.8	80	T-40	0.07
SWC10.0X240	75373	55838765	76775		240	160	17.8	80	T-40	0.076
SWC10.0X260	75374	55838841	76776		260	180	17.8	80	T-40	0.082
SWC10.0X280	75375	55838856	76778		280	200	17.8	80	T-40	0.088
SWC10.0X300	75376	55838773	76780		300	220	17.8	80	T-40	0.094
SWC10.0X320	75377	55836226	72185		320	240	17.8	80	T-40	0.1
SWC10.0X340	75378	55838784	72020		340	260	17.8	80	T-40	0.11
SWC10.0X360	75379	55838860	72021		360	280	17.8	80	T-40	0.11
SWC10.0X380	75380	55838875	72022		380	300	17.8	80	T-40	0.12
SWC10.0X400	75381	55838792	72023		400	320	17.8	80	T-40	0.12

SWC
Structural Countersunk Wood Screw

Product characteristic properties

Tuotenro	Product characteristic properties					
	Characteristic Yield Moment – $M_{y,k}$ [$M_{y,k}$] [Nm]	Characteristic withdrawal parameter – $f_{ax,k,90^\circ}$ [$f_{ax,k,90^\circ}$] [N/mm ²]	Characteristic head pull-through parameter – $f_{head,k}$ [$f_{head,k}$] [N/mm ²]	Characteristic tensile capacity – $f_{tens,k}$ [$f_{tens,k}$] [kN]	Characteristic torsional strength – $f_{tor,k}$ [$f_{tor,k}$] [Nm]	Torsional ratio
SWC6.0X200	10.5	13	11.9	12.3	11	≥ 1,5
SWC6.0X220	10.5	13	11.9	12.3	11	≥ 1,5
SWC6.0X240	10.5	13	11.9	12.3	11	≥ 1,5
SWC6.0X260	10.5	13	11.9	12.3	11	≥ 1,5
SWC6.0X280	10.5	13	11.9	12.3	11	≥ 1,5
SWC6.0X300	10.5	13	11.9	12.3	11	≥ 1,5
SWC8.0X80	25.9	12.6	12.5	23.7	27.4	≥ 1,5
SWC8.0X100	25.9	12.6	12.5	23.7	27.4	≥ 1,5
SWC8.0X120	25.9	12.6	12.5	23.7	27.4	≥ 1,5
SWC8.0X140	25.9	12.6	12.5	23.7	27.4	≥ 1,5
SWC8.0X160	25.9	12.6	12.5	23.7	27.4	≥ 1,5
SWC8.0X180	25.9	12.6	12.5	23.7	27.4	≥ 1,5
SWC8.0X200	25.9	12.6	12.5	23.7	27.4	≥ 1,5
SWC8.0X220	25.9	12.6	12.5	23.7	27.4	≥ 1,5
SWC8.0X240	25.9	12.6	12.5	23.7	27.4	≥ 1,5
SWC8.0X260	25.9	12.6	12.5	23.7	27.4	≥ 1,5
SWC8.0X280	25.9	12.6	12.5	23.7	27.4	≥ 1,5
SWC8.0X300	25.9	12.6	12.5	23.7	27.4	≥ 1,5
SWC8.0X320	25.9	12.6	12.5	23.7	27.4	≥ 1,5
SWC8.0X340	25.9	12.6	12.5	23.7	27.4	≥ 1,5
SWC8.0X360	25.9	12.6	12.5	23.7	27.4	≥ 1,5
SWC8.0X380	25.9	12.6	12.5	23.7	27.4	≥ 1,5
SWC8.0X400	25.9	12.6	12.5	23.7	27.4	≥ 1,5
SWC10.0X100	43.7	12.2	11.2	33.8	48.9	≥ 1,5
SWC10.0X120	43.7	12.2	11.2	33.8	48.9	≥ 1,5
SWC10.0X140	43.7	12.2	11.2	33.8	48.9	≥ 1,5
SWC10.0X160	43.7	12.2	11.2	33.8	48.9	≥ 1,5
SWC10.0X180	43.7	12.2	11.2	33.8	48.9	≥ 1,5
SWC10.0X200	43.7	12.2	11.2	33.8	48.9	≥ 1,5
SWC10.0X220	43.7	12.2	11.2	33.8	48.9	≥ 1,5
SWC10.0X240	43.7	12.2	11.2	33.8	48.9	≥ 1,5
SWC10.0X260	43.7	12.2	11.2	33.8	48.9	≥ 1,5
SWC10.0X280	43.7	12.2	11.2	33.8	48.9	≥ 1,5
SWC10.0X300	43.7	12.2	11.2	33.8	48.9	≥ 1,5
SWC10.0X320	43.7	12.2	11.2	33.8	48.9	≥ 1,5
SWC10.0X340	43.7	12.2	11.2	33.8	48.9	≥ 1,5
SWC10.0X360	43.7	12.2	11.2	33.8	48.9	≥ 1,5
SWC10.0X380	43.7	12.2	11.2	33.8	48.9	≥ 1,5
SWC10.0X400	43.7	12.2	11.2	33.8	48.9	≥ 1,5

Tekniset tiedot

SWC Structural Countersunk Wood Screw

SIMPSON

Strong-Tie

Simpson Strong-Tie / Gbo Fastening Systems AB
Bruksvägen 2, 593 75 Gunnebo
tel: 0490-300 00
fax : 0490-233 00

Copyright by Simpson Strong-Tie®
Tämän materiaalin tiedot ovat yksinomaan Simpson Strong-Tie:n © omaisuutta
Tiedot ovat voimassa ja käytettävissä ainoastaan Simpson –Strong-Tie:n © tuotteita käytettäessä.

SWC Structural Countersunk Wood Screw



www.strongtie.fi

SIMPSON

Strong-Tie

2025-08-19