

Tekniset tiedot

SIMPSON

Strong-Tie

FARMA

Steel Roofing and Cladding to Steel Screw

FARMA farmer screws are used for fixing overlapping wall and roof metal sheeting. Drilling capacity is 2.0 x 1.0 mm.

AL

OUTDOOR

Ominaisuudet

Features:

- 8 mm hex head
- Drill point
- Painted head
- EPDM washer
- Aluminium



Colors:

- 75309 = Black painted head RAL 9005
- 75310 = White painted head RAL 9010

Sovellus

Application:

- Steel to steel



FARMA
Steel Roofing and Cladding to Steel Screw

Technical Data



Product dimensions Painted Head RAL 9005

Tuotenro	Item code	NOBB nr.	Fastener dimensions [mm]						
			d	l	d _h	l _g	t _{fix}	bit	
FARMA5.5X35 RAL9005	75309	55838243	5.5	35	14	32	2	SW8	



Product dimensions Painted Head RAL 9010

Tuotenro	Item code	DB nr.	NOBB nr.	Fastener dimensions [mm]							Qty/box
				d	l	d _h	d ₁	l _g	t _{fix}	bit	
FARMA5.5X35 RAL9010	75310	2055670	55836113	5.5	35	14	4	32	2	SW8	250

