

LSF Skirting Screw

Used indoors for fixing skirting to underlying wood material. The small screw head has ribs on its underside for easy countersinking and a cutpoint to counteract splitting of the woodwork. The screw can also be fixed to a steel base with a maximum thickness of 0.6mm.

Ominaisuudet

Benefits

- Cylindrical embedding head: discreet finish
- Its design allows for a perfect finish and limits noise

Sovellus

Support

- Skirting to wood
- Skirting to steel




LSF
Skirting Screw

Technical Data

Product dimensions



Tuotenro	Item code	Fastener dimensions [mm]						Paino [kg]
		d	l	d _h	l _g	t _{fix}	bit	
LSF3.0X35	75319	3	35	5.5	23	12	TX10	0.002
LSF3.0X42	75321		42	5.5	27	15	TX10	0.002
LSF3.0X57	75322		57	5.5	37	20	TX10	0.003



Painted Head RAL 9010

Tuotenro	Item code	DB nr.	NOBB nr.	Fastener dimensions [mm]							Qty/box
				d	l	d _h	d ₁	l _g	t _{fix}	bit	
LSF3.0X42 RAL9010	75323	2055682	55836158	3	42	5.5	2	27	15	TX10	200
LSF3.0X57 RAL9010	75324	2055683	55836162		57	5.5	2	37	20	TX10	200

