

Tekniset tiedot

FBCS Fibre Cement Screw

SIMPSON**Strong-Tie**

FBCS screws are used in humid conditions both indoor and outdoor. They are particularly suited for fixing fibre cement boards to wood or steel joists with a maximum thickness of 1.0 mm.

Ominaisuudet

Materiaali

- Korroosiosuoja: Impreg[®]+


Hyödyt

- PH drive
- Countersunk head with ribs
- Sharp point
- Impreg[®]+ coating

Sovellus

Liitos



- Fibre cement to steel or wood



FBCS
Fibre Cement Screw

Technical Data

Mitat



Tuotenro	Item code	Fastener dimensions [mm]						Bit	Paino [kg]
		d	l	d _h	d ₁	l _g	t _{fix}		
FBCS3.9X25	75453	3.9	25	6.8	2.4	18	15	PH2	0.001
FBCS3.9X35	75454		35	6.8	2.4	28	26	PH2	0.002

FBCS Collated Screws

Tuotenro	Item code	DB nr.	NOBB nr.	Fastener dimensions [mm]									Bit	Box Quantity
				d	l	d _h	d ₁	A _h	h _t	l _g	l _p	t _{fix}		
FBCS3.9X25 Collated	75719	2056066	55836601	3.9	25	6.8	2.4	-	-	18	-	15	PH2	1000
FBCS3.9X35 Collated	75720	2056067	55836597	3.9	35	6.8	2.4	-	-	28	-	26	PH2	1000

* Flat tape collated for standard auto-feed screwdrivers
Also available Quik Drive collated

