Tekniset tiedot

CLSZN
Wood Facade Screw Impreg®+

Made for outdoor wood cladding. The flat head with fiber lock technology protects the wood from moisture, and the double thread ensures sufficient insertion, even in high density wood without the risk of spin-off. Impreg®+ version is made for painted facades

Ominaisuudet

Materiaali

- Korroosiosuoja: Impreg®+

Features:

- 6 lobe drive
- Flat head with fiber lock technology
- Double threaded
- Extreme ductility

Sovellus

Sovellus

- Wood facades to wood
- ***WARNING :*** For applications with timber classes T4 or higher and especially with acid timber pH < 4 (Douglas), we recommend the CLS A4 stainless steel version.

Technical Data

Mitat



Tuotenro	Item code	Mitat [mm]						
		d	l	d_h	l_{g1}	l_{g2}	t_{fix}	bit
CLSZN4.8X48	75460	4.8	48	8	26	18	23	T-20
CLSZN4.8X48 Bulk	75459		48	8	26	18	23	T-20
CLSZN4.8X65	75462		65	8	26	22	40	T-20
CLSZN4.8X65 Bulk	75461		65	8	26	22	40	T-20

Simpson Strong-Tie / Gbo Fastening Systems AB
Bruksvägen 2, 593 75 Gunnebo
tel: 0490-300 00
fax : 0490-233 00

Copyright by Simpson Strong-Tie®
Tämän materiaalin tiedot ovat yksinomaan Simpson Strong-Tie:n © omaisuutta
Tiedot ovat voimassa ja käytettävissä ainoastaan Simpson –Strong-Tie:n © tuotteita käytettäessä.