

Tekniset tiedot

BASN17G

Framing Nail 17° Plastic Strip - Round Head, Barbed shank - HDG

SIMPSON

Strong-Tie

The framing nail is used for wood to wood constructions. The round head gives a good visual end result and the plastic collation is not sensitive for wetness. The barbed shank increases withdrawal resistance.

Ominaisuudet

Features:

- Round head
- Barbed shank increases withdrawal resistance
- Plastic strip 17°

Sovellus

Application:

- Framing wood to wood

CE



HDG
50 µm

OUTDOOR





BASN17G

Framing Nail 17° Plastic Strip - Round Head, Barbed shank - HDG


Technical Data

Product dimension



Tuotenro	Item code	Fastener dimensions [mm]			
		d	l	d _h	t _{fix}
BASN17G2.8X50	75621	2.8	49.5	6.6	32.7
BASN17G2.8X55	75622		54.5	6.6	37.7
BASN17G2.8X65	75623		63.5	6.6	46.7
BASN17G2.8X75	75624 - 75619		73.5	6.6	56.7
BASN17G3.1X90	75625 - 75620	3	88	6.6	70

Product characteristic parameters



Tuotenro	Product characteristic properties			
	Characteristic Yield Moment – M _{y,k} [M _{y,k}] [Nm]	Characteristic withdrawal parameter – f _{ax,k,90°} [f _{ax,k,90°}] [N/mm ²]	Characteristic head pull-through parameter – f _{head,k} [f _{head,k}] [N/mm ²]	Characteristic tensile capacity – f _{tens,k} [f _{tens,k}] [kN]
BASN17G2.8X50	2.6	4.9	22.6	4
BASN17G2.8X55	2.6	4.9	22.6	4
BASN17G2.8X65	2.6	4.9	22.6	4
BASN17G2.8X75	2.6	4.9	22.6	4
BASN17G3.1X90	3.9	5.4	20.9	4.8

