

BASN21G

Framing Nail 21° Plastic Strip - Round Head, Barbed shank - HDG

The framing nail is used for wood to wood constructions. The round head gives a good visual end result and the plastic collation is not sensitive for wetness. The barbed shank increases withdrawal resistance.

Ominaisuuudet

Advantages

- Round head
- Barbed shank increases withdrawal resistance
- Plastic strip 21°

Sovellus

Support

- Framing wood to wood





BASN21G

Framing Nail 21° Plastic Strip - Round Head, Barbed shank - HDG


Technical Data

Product dimensions



Tuotenro	Item code	Fastener dimensions [mm]				Paino [kg]
		d	l	d _h	t _{fix}	
BASN21G2.8X50	75626	2.8	49.5	6.6	32.7	0.003
BASN21G2.8X55	75627		54.5	6.6	37.7	0.003
BASN21G2.8X65	75628		63.5	6.6	46.7	1.7
BASN21G2.8X75	75629 - 75630		73.5	6.6	56.7	0.004
BASN21G3.1X90	75631 - 75632	3	88	6.6	70	0.006

Product characteristic parameters



Tuotenro	Product characteristic properties			
	Characteristic Yield Moment – M _{y,k} [M _{y,k}] [Nm]	Characteristic withdrawal parameter – f _{ax,k,90°} [f _{ax,k,90°}] [N/mm ²]	Characteristic head pull-through parameter – f _{head,k} [f _{head,k}] [N/mm ²]	Characteristic tensile capacity – f _{tens,k} [f _{tens,k}] [kN]
BASN21G2.8X50	2.6	4.9	22.6	4
BASN21G2.8X55	2.6	4.9	22.6	4
BASN21G2.8X65	2.6	4.9	22.6	4
BASN21G2.8X75	2.6	4.9	22.6	4
BASN21G3.1X90	3.9	5.4	20.9	4.8

