

Tekniset tiedot


SIMPSON

Strong-Tie

ARA2C - W

Ring shank nail - Stainless Steel A2 + Painted NCS 0502-Y (White)

Stainless steel ring shank nails can be installed in outdoor environments. Used where high withdrawal strength is required. A common use is in the construction of jetties, thanks to the nail's corrosion resistance. When laying a brick facade the joints are anchored to an existing cross-wall up to 6 m.



Ominaisuudet

Features:

- Low oval head
- Ring shank
- A2 stainless steel

Sovellus

Sovellus

- Puu-puu



Tekniset tiedot



SIMPSON**Strong-Tie®**

ARA2C - W

**Ring shank nail - Stainless Steel A2 + Painted NCS 0502-Y
(White)**


Technical Data

Mitat



Tuotenro	Item code	Mitat [mm]			
		d	l	d _h	t _{fix}
ARA2C2.3x35W	75617	2.3	35	5.5	21.2

Tuotteen ominaisuudet



Tuotenro	Tuotteen ominaisuudet			
	Taivutuslujuus - M _{y,k} [Nm] [M _{y,k}] [Nm]	Tyypillinen vetoparametri - f _{ax,k,90°} [N/mm²] [f _{ax,k,90°}] [N/mm²]	Tyypillinen läpivetoparametri - f _{head,k} [N/mm²] [f _{head,k}] [N/mm²]	Tyypillinen vetolujuus - f _{tens,k} [kN] [f _{tens,k}] [kN]
ARA2C2.3x35W	1.8	6.2	29.3	3.2

Simpson Strong-Tie / Gbo
Fastening Systems AB
Bruksvägen 2, 593 75 Gunnebo
tel: 0490-300 00
fax : 0490-233 00

Copyright by Simpson Strong-Tie®

Tämän materiaalin tiedot ovat yksinomaan Simpson Strong-Tie:n © omaisuutta

Tiedot ovat voimassa ja käytettävissä ainoastaan Simpson Strong-Tie:n © tuotteita käytettäessä.

ARA2C - W

**Ring shank nail - Stainless Steel A2 + Painted
NCS 0502-Y (White)**

2025-04-30

www.strongtie.fi

SIMPSON**Strong-Tie®**