

BPTD

Strap tie down Bandlock® Pro

Bandlock® Pro BPTD tie down is used to connect a tension strap to a M12 threaded rod. The innovative click system makes installation easy and a builder can save approx. 5 mins installation time per connector compared to traditional tie downs. BPTD fits straps with the width 25, 40 and 60 mm.

Ominaisuudet

Materiaali

- Teräslaatu:
Kuumasinkitty teräs S250GD + Z275 EN 10346 mukaan
- Korroosiosuoja:
275 g/m² molemmin puolin - vastaa noin 20 µm:n sinkkikerrosta





Hyödyt

- Easy installation
- No bolts and nuts
- Timesaving compared to other tie downs
- Can be used with 25, 40 and 60 mm straps
- Easy to understand

Sovellus

Käyttötarkoitus

- For stabilizing and anchoring roof constructions and buildings




BPTD

Strap tie down Bandlock® Pro

Technical Data

Product dimensions



Tuotenro	Product dimensions [mm]			Box Quantity	Paino [kg]
	A	B	t		
BPTD	51	180	2.5	10	0.32

Product capacities

Tuotenro	Product capacities	
	Threaded rod	Characteristic capacities [kN]
		$R_{1,k}$
BPTD	M12	27.5

The values are with all 6 pins in use and 2 bended

BPTD

Strap tie down Bandlock® Pro

Asennus

Kiinnittäminen

- The BPTD must be fastened at least 10 mm onto the threaded rod
- Connect the windbracing strap to the BPTD and click the connector shut
- Bend the 2 longest pins
- Screw the BPTD further onto the threaded rod to tighten the tension strap.
- IMPORTANT - by installation of 60 mm straps, the corners of the strap has to be trimmed so that all 6 pins in the tightener can be used, see installation pics below.

