

Tekniset tiedot

SIMPSON

Strong-Tie

CNA-G

Connector Nail Hot-Dip Galvanised

Hot-dip galvanised annular ring-shank connector nails are recommended for structural assemblies and installation of Simpson Strong-Tie connectors to wood, in order to obtain the published load bearing capacities.

CE



HDG
50 µm

Ominaisuudet


Advantages

- The conical shape under the head ensures that the nail is fully in contact with the hole
- Length of nail is stamped on the head
- High withdrawal capacity
- Annular ring thread

Sovellus

Support

- Connector to wood



CNA-G
Connector Nail Hot-Dip Galvanised

Technical Data

Materiale

Hot-dip galvanised steel

Product Dimensions



Tuotenro	Fastener dimensions [mm]					
	d	l	d _h	l _g	Qty per box	Qty per outer box
CNA4.0X40G	4	40	7	30	250	8

Simpson Strong-Tie / Gbo Fastening Systems AB
Bruksvägen 2, 593 75 Gunnebo
tel: 0490-300 00
fax : 0490-233 00

CNA-G
Connector Nail Hot-Dip Galvanised



SIMPSON

Strong-Tie®

Copyright by Simpson Strong-Tie®
Tämän materiaalin tiedot ovat yksinomaan Simpson Strong-Tie:n © omaisuutta
Tiedot ovat voimassa ja käytettävissä ainoastaan Simpson –Strong-Tie:n © tuotteita käytettäessä.

2024-04-20

www.strongtie.fi