

CLR Plus H Hex-Head Concrete Screws

The hexagonal head version is the standard version used for the most applications, specially with greatest diameters and highest loads to fix metallic and timber carpentry.


Sovellus

Material

- Electro-galvanized steel

Suitable on

- Cracked and uncracked concrete



Technical Data

CLR Plus H

Hex-Head Concrete Screws

Product dimensions

Tuotenro	Item code	Type [d x L]	Hole diameter	Fixing thickness for reduced embedment depth	Fixing thickness for standard embedment depth	Fixing thickness for increased embedment depth	Qty per box	Qty per outer box
CLR Plus H 6x40	72105B0604000	6x40	6	5	-	-	100	1000
CLR Plus H 6x50	72105B0605000	6x50	6	15	10	-	100	400
CLR Plus H 6x60	72105B0606000	6x60	6	25	20	5	100	1000
CLR Plus H 6x80	72105B0608000	6x80	6	45	40	25	100	1000
CLR Plus H 6x100	72105B0610000	6x100	6	65	60	45	100	1000
CLR Plus H 8x60	72105B0806000	8x60	8	15	5	-	50	500
CLR Plus H 8x80	72105B0808000	8x80	8	35	25	15	50	500
CLR Plus H 8x100	72105B0810000	8x100	8	55	45	35	50	250
CLR Plus H 8x120	72105B0812000	8x120	8	75	65	55	50	250
CLR Plus H 8x140	72105B0814000	8x140	8	95	85	75	50	250
CLR Plus H 10x60	72105B1006000	10x60	10	5	-	-	50	200
CLR Plus H 10x80	72105B1008000	10x80	10	25	5	-	50	250
CLR Plus H 10x100	72105B1010000	10x100	10	45	25	15	40	200
CLR Plus H 10x120	72105B1012000	10x120	10	65	45	35	50	200
CLR Plus H 10x140	72105B1014000	10x140	10	85	65	55	30	150
CLR Plus H 10x150	72105B1015000	10x150	10	95	75	65	50	200
CLR Plus H 10x160	72105B1016000	10x160	10	105	85	75	50	200
CLR Plus H 10x200	72105B1020000	10x200	10	145	125	115	25	100
CLR Plus H 10x240	72105B1024000	10x240	10	185	165	155	25	100
CLR Plus H 10x280	72105B1028000	10x280	10	225	205	195	25	100
CLR Plus H 10x320	72105B1032000	10x320	10	265	245	235	25	100
CLR Plus H 10x400	72105B1040000	10x400	10	345	325	315	25	-
CLR Plus H 12x80	72105B1208000	12x80	12	15	-	-	25	250
CLR Plus H 12x110	72105B1211000	12x110	12	45	25	10	25	100
CLR Plus H 12x130	72105B1213000	12x130	12	65	45	30	25	100
CLR Plus H 12x150	72105B1215000	12x150	12	85	65	50	25	100
CLR Plus H 14x80	72105B1408000	14x80	14	5	-	-	25	100

Tekniset tiedot

SIMPSON**Strong-Tie**

CLR Plus H Hex-Head Concrete Screws

Tuotenro	Item code	Type [d x L]	Hole diameter	Fixing thickness for reduced embedment depth	Fixing thickness for standard embedment depth	Fixing thickness for increased embedment depth	Qty per box	Qty per outer box
CLR Plus H 14x110	72105B1411000	14x110	14	35	10	-	25	100
CLR Plus H 14x130	72105B1413000	14x130	14	55	30	15	25	100
CLR Plus H 14x150	72105B1415000	14x150	14	75	50	35	25	100

Simpson Strong-Tie / Gbo Fastening Systems AB
Bruksvägen 2, 593 75 Gunnebo
tel: 0490-300 00
fax : 0490-233 00

Copyright by Simpson Strong-Tie®
Tämän materiaalin tiedot ovat yksinomaan Simpson Strong-Tie:n © omaisuutta
Tiedot ovat voimassa ja käytettävissä ainoastaan Simpson –Strong-Tie:n © tuotteita käytettäessä.

CLR Plus H Hex-Head Concrete Screws



2026-08-20

www.strongtie.fi**SIMPSON****Strong-Tie**